

MEGAMAN®

# THE MEGAMAN®

# LIGHTING CATALOGUE

V04



[www.megamanuk.com](http://www.megamanuk.com)

MEGAMAN® is a global brand in high-performance, energy-efficient lighting and an innovative leader in the use of LED with design and technology that targets the best eco-lighting solutions. Megaman products are widely distributed throughout the world, including Europe, Asia Pacific, Middle East, North America and Latin America, covering more than 90 countries. By setting environmental management as one of the company's highest priorities, Megaman is focusing on eco-friendly environmental processes from initial design, to manufacturing, research and development, and the disposal or recycling of its products.



## MEGAMAN®

Megaman (UK) Limited  
Megaman House  
2 Quadrant Park  
Mundells  
Welwyn Garden City  
Herts AL7 1FS

T: +44 (0)1707 386000  
F: +44 (0)1707 386001  
E: [sales@megamanuk.com](mailto:sales@megamanuk.com)



Follow us  
[@megamanukltd](https://twitter.com/megamanukltd)

© MEGAMAN® (UK) LTD APRIL 2022

All information stated is correct at the time of printing and subject to change without prior notice.





Providing flexible lighting solutions for a wide range of indoor and outdoor applications, introducing MEGAMAN®'s new and improved fixture and lamp portfolio.

For adaptable, high-performance fixture solutions, look no further than our new Performa range. Combining quality materials and value-added features like motion sensors, emergency compatibility, dual beam (DBT) and colour change technology (CCT), performance is at the heart of all Performa solutions.

For cost-effective, staple products, the Essentials range should be every contractor and wholesaler's go-to. Providing reliability over innovation, Essentials solutions are there for the day-to-day, delivering in terms of cost and results for both retrofit and new-build installations.

Collectively these two ranges provide you with more choice and echo Megaman's long-standing LED lamp collections - Professional and Economy - with a product for every eventuality.

Designed with ease of installation in mind, these new fixture ranges emphasise our ongoing commitment to supporting and making life easier for our contractors and stockists. Simple, one-box solutions, they're ideal to keep in the back of the van; but our wholesalers' and ease of stock control was also at the forefront during product development.

**MEGAMAN®**  
**Performa**  
 FIXTURE RANGE  
 HIGH PERFORMANCE & QUALITY FROM MEGAMAN®

**essentials** **MEGAMAN®**  
 + VALUE FOR MONEY + RELIABLE + EVERYDAY + LED FIXTURES +



## MEGAMAN® UK-WIDE SALES TEAM


The Megaman Business Development team have been specifically trained to enhance our relationship with our customers and to ensure that we offer the individual support that they require.

Technical product advice and suggestions to ensure that the correct lighting solutions are selected for each clients requirements.

Recommendations on how to reduce energy consumption and save on energy bills.

Help in lowering carbon emissions to meet Government targets and fulfil ISO accreditations.

Advice on changes in regulations.  
Guidance on new lamp and lighting technologies.



**SCOTLAND, N. IRELAND, ISLE OF MAN & REPUBLIC OF IRELAND**  
CONTACT: 07931 817211

**NORTH ENGLAND**  
CONTACT: 07958 172109

**WALES & WEST MIDLANDS**  
CONTACT: 07931 817212

**EAST MIDLANDS & ANGLIA**  
CONTACT: 07813 695891

**LONDON & SOUTH EAST**  
CONTACT: 07976 620377

**SOUTH WEST**  
CONTACT: 07811 144540

BRINGING  
A SMARTER  
LIFE IN LIGHT

# CONTENTS

MEGAMAN®  
**Performa**  
FIXTURE RANGE  
HIGH PERFORMANCE & QUALITY FROM MEGAMAN®

PERFORMA | LED FIXTURES

4-33

PERFORMA | LED TRACK LIGHTING

34-43

PERFORMA | TEMPUS® EMERGENCY SELF-TEST

44-57

essentials MEGAMAN®  
A RANGE OF ENVIRONMENTAL, REGULATORY, QUALITY & LED FIXTURES

ESSENTIALS | LED FIXTURES RANGE

58-81























ESSENTIALS | TEMPUS® EMERGENCY LIGHTING

82-93

LED LAMPS | PROFESSIONAL & ECONOMY

94-160

## KEY

 IP RATING	 IMPACT RATING	 WARRANTY PERIOD	 FLICKER FREE	 SHATTER PROOF	 GLARE RATING
 MICROWAVE MOTION FUNCTION	 ELECTRICAL CLASS RATING	 PRODUCT DISCOUNT GROUP	 LIGHT DISTRIBUTION	 SWITCHABLE BEAM ANGLE	 COLOUR CHANGING FUNCTION
 DIMMING FUNCTION	 UNIVERSAL DIMMING	 HIGH CRI RATING	 ACOUSTIC RATING	 PIR SENSOR FUNCTION	 MICROWAVE MOTION SENSOR
 VARIABLE POWER OUTPUT	 EMERGENCY FUNCTION	 PUSH-FIT CONNECTION	 ENERGY RATING	 BOX QUANTITY	 LIGHT APPEARANCE

# LED FIXTURES

MEGAMAN® offers a full spectrum of LED FIXTURES for applications such as retail, hotels, restaurants, homes and offices; and even the highly harsh and demanding modern intensive animal farming environments.



# MEGAMAN® PERFORMA | LED FIXTURES RANGE



BERTO SIDELIT LED PANEL P6



GABIO LED PENDANT P8



GEO 2 LED HIGH BAY P10



TOTT 2 LED FLOODLIGHT P12



RENZO MODULAR LED BULKHEAD P14



FONDA OUTDOOR LED BULKHEAD P16



TONO INDOOR LED BATTEN P18



FARRON INDOOR LED BATTEN P20



DINO 2 INDOOR & OUTDOOR LED BATTEN P22



DINO 2 CHEMICAL RESISTANT LED BATTEN P24



TEGO 2 FIRE-RATED LED DOWNLIGHT P26



TEGO FIRE-RATED DOWNLIGHT P28



MILENA RECESSED LED DOWNLIGHT P30

## COMMERCIAL | LED PANEL

# BERTO

ULTRA SLIMLINE HIGH PERFORMANCE & MAINTENANCE FREE **BERTO SIDELIT TPb LED PANELS** DELIVER A FLICKER FREE AND LOW GLARE EVEN LIGHT DISTRIBUTION THAT'S SUITABLE FOR MULTIPLE APPLICATIONS.

### FEATURES & BENEFITS

- High performance Sidelit TPb LED  $\leq$ UGR22 panels
- Comes with non dimming driver
- Surface and suspension mounting kits available separately
- 110° beam angle
- 50,000 hours rated life
- Up to 100 lumen per system watt efficacy
- Perfect for shallow ceiling voids
- Quick & easy installation
- Lightweight LED panel with non discolouring TPb rated diffusers
- Suitable for use in exposed T-grid ceilings
- Ideal for general lighting use
- Long maintenance period and low lumen depreciation
- Can be used as part of a Part L building compliance



### Applications

- Shopping centres
- Retail stores
- Hospitals
- General lighting

### ACCESSORIES



**710502SIDELIT**  
Emergency Kit  
for Sidelit panels



**130214**  
Suspension Kit  
for Panel, 1.0m



**130212**  
Suspension Kit  
for Panel, 1.8m



**710941**  
DALi Driver  
199x55x24.5mm



**130344**  
Loop Through  
Junction Box  
with 3 Pin



**710933**  
Surface Mounted  
Frame  
600x600x64mm



LED FIXTURES WITH  
INNOVATIVE ADDED  
VALUE FEATURES

**MEGAMAN®**  
**Performa**  
 FIXTURE RANGE  
 HIGH PERFORMANCE & QUALITY FROM MEGAMAN®



## COMMERCIAL | LED PANEL

# BERTO SQUARE SIDELIT TPb LED PANEL

36W | 4000K/6500K | 3600lm | 50,000hrs | Non-Dim Driver



ULTRA SLIM PROFILE

EASY PUSH-FIT CONNECTOR

FLICKER FREE





TPb  
SIDELIT



**Photometric data:**  
 Please refer to our website for up to date photometric information.

### DIMENSIONS



Loop through wiring adaptor

### MEGAMAN® PERFORMA BERTO

**SIDELIT TPb** panel is an integrated LED lighting solution that facilitates easy installation and maintenance. It delivers a high luminous efficacy up to 100lm/W – matching the lighting levels of 3 x 18W T8 and 3 x 24W HE T5 fluorescent modular fittings.



BRINGING YOU  
MORE CHOICE!

See page 60 for MEGAMAN® ESSENTIALS BERTO BACKLIT LED PANEL economy option.

Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Dimensions (LxWxH mm)
<b>130340</b> UGR22 TPb SIDELIT (SQUARE) X1 PANEL	36W	4000K / 80	3600	N	110°	50,000	595x595x13
<b>130342</b> UGR22 TPb SIDELIT (SQUARE) X1 PANEL	36W	6500K / 80	3600	N	110°	50,000	595x595x13

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## COMMERCIAL | PENDANT

# GABIO

### FEATURES & BENEFITS

- Louvre cell design with low glare rating of UGR19
- Wide batwing light distribution and wide beam angle
- Built-in LED driver
- Range of mounting methods available
- Modular joint system available
- Lit louvres in the module junctions
- High level of visual comfort, ideal for individual task lighting
- High uniformity of light
- Easy installation
- Suitable for a range of different applications
- Create a range of different product profiles
- Unique design feature of a continuous line of light

### ACCESSORIES



**190574** GABIO  
Transparent Main  
Supply Wire




**190576** GABIO  
Square Ceiling  
Rose



**190578** GABIO  
2 x 1.5M  
Suspension wire



**190580** GABIO  
Linear Joint



**190586** GABIO  
X-Joint 4000K



**190582** GABIO  
L-Joint 4000K



**190584** GABIO  
T-Joint 4000K



**190588** GABIO  
Suspension Kit -  
DALI Version

**SLIM DESIGN GABIO IS AN ALUMINIUM LINEAR SUSPENDED AND SURFACE MOUNTED PENDANT WITH A MODULAR JOINT SYSTEM; THAT CREATES A SEAMLESS LINE OF HIGH QUALITY AND EVEN LIGHT.**

**CALL:** 01707 386000  
**EMAIL:** SALES@MEGAMANUK.COM

## COMMERCIAL | PENDANT

# GABIO INTEGRATED LED PENDANT

20W-30W | 4000K | 2000-3500lm | 50,000hrs | Built-in LED Driver



**LINEAR SLIM PROFILE**

**SEAMLESS LIGHT SYSTEM**


**LOUVRE CELL DESIGN**



**Photometric data:**  
 Please refer to our website for up to date photometric information.

**MEGAMAN® PERFORMA GABIO** offers a slim aluminium linear profile and understated design which is suitable for any interior installation. Its unrivalled adaptability and seamless light system makes Gabio the perfect choice for most applications.

### DIMENSIONS



LED FIXTURES WITH  
 INNOVATIVE ADDED  
 VALUE FEATURES

Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxWxH mm)
<b>190550</b>	20W	4000K / 80	2000 (with driver)	N	90°	50,000	1347	1142x57x56
<b>190552</b>	30W	4000K / 80	3500 (with driver)	N	90°	50,000	1362	1142x57x56
<b>190554</b>	30W	4000K / 80	3500 (1000 Up/ 2500 Down)	N	90°	50,000	1362	1142x57x56
<b>190556</b>	30W	4000K / 80	3500 (Dali)	N	90°	50,000	1362	1142x57x56

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C


## INDUSTRIAL | HIGH BAY

# GEO2

5 Selectable  
lumen outputs



IN-LINE FLEX CONNECTOR  
WITH PUSH FIT



Microwave  
Sensor  
Module  
option



## MEGAMAN®'S NEW VARIABLE WATTAGE & REMOTE CONTROLLABLE POWERFUL LED HIGH BAY

### FEATURES & BENEFITS

- Passive cooling structure
- Excellent heat dissipation with graphene housing
- Easy installation with single point hook mounting design
- Eye hook included
- IP65 protection
- Anti-surge protected fitting
- In-line flex connector with push fit. Allows PCR2000 flex to be connected without using additional adaptable box. Reducing installation time dramatically
- 50,000hrs L70B50 at Ta40°C
- Compatible with microwave sensor
- Flicker free to avoid stroboscopic effect with rotating machines.
- High vandal resistant with IK08
- Reflector & refractor as optional accessories
- Counter balance included with Microwave Motion Sensor to ensure balanced instal

### ACCESSORIES



**710729** GEO 2  
Microwave  
Motion Sensor



**710871** GEO 2  
0-10V Dimming  
wire 300mm



**190706** 70°  
Polycarbonate  
Reflector



**190704** 90°  
Aluminium  
Reflector



**710842** GEO 2  
Motion Sensor  
Remote Control

### Applications

- High-ceiling areas
- Warehouses
- Manufacturing
- Halls



LED FIXTURES WITH  
INNOVATIVE ADDED  
VALUE FEATURES

## INDUSTRIAL | HIGH BAY

# GEO 2 IP65 LED HIGH BAY with Selectable Wattage

70-150W | 4000K | 10500-21000lm | 50,000hrs | Dimmable



REMOTE CONTROLLABLE SENSOR

COMPATIBLE WITH MICROWAVE SENSOR

FLICKER FREE



**Photometric data:**  
Please refer to our website for up to date photometric information.


**MEGAMAN®'s PERFORMA GEO 2** is a highly flexible remote controllable high bay fixture with variable wattage output and a robust IP65 & IK08 passive cooling structure.

New GEO 2 is an innovative high performance LED high bay fixture, that is designed for an easy single point, low labour cost installation. An ideal powerful energy saving lighting solution for large areas with some of today's most demanding environments.



See page 62 for MEGAMAN® ESSENTIALS LED HIGH BAY (KEO) economy option.

### DIMENSIONS



#### 5 Selectable Outputs

- 70W - 10500lm
- 90W - 13500lm
- 100W - 15000lm
- 125W - 18900lm
- 150W - 21000lm

Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (H x Dia mm)
<b>710931</b>	70/90/100 125/150W	4000K / 80	10500/13500/15000 18900/21000	Y	110°	50,000	1347	201x300

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## INDUSTRIAL | FLOODLIGHT

# TOTT 2

**MEGAMAN® PERFORMA**  
**TOTT 2. A NEW TOUGH**  
**IP65 & IK08 CORROSION**  
**AND UV RESISTANT**  
**VERSATILE RANGE OF**  
**LED FLOODLIGHTS.**

### FEATURES & BENEFITS

- Slim and extra light weight
- Non pre-flexed and push to fit connectors
- Textured diffuser
- Available in 4 different sizes
- Polymeric rust free housing
- IP65 and IK08 rated
- Adjustable fixing bracket  $\pm 355^\circ$
- Wide area floodlight without glare
- Simple installation
- Suitable for outdoor use
- Flexible tilting and positioning
- Corrosion free & UV resistant housing



**710889** - 9.5W



**710890** - 24W



**710891** - 45W



**710677** - 85W

### ACCESSORIES



**710830 TOTT 2**  
 PIR Sensor.  
 Compatible with  
 710890, 710891 &  
 710677



**180294 TOTT 2**  
 Outreach Arm

#### Applications

- Commercial
- Domestic outdoor security lighting
- Signage
- Billboards
- Pillar facades
- Gate areas
- Retail



**PIR Sensor option** for additional security and energy saving. IP65 sealed construction.

Compatible with 24W, 45W & 85W versions.

- **FAST FIT**
- **PLUG+PLAY**
- **TOOLLESS INSTALL**



**CALL:** 01707 386000  
**EMAIL:** SALES@MEGAMANUK.COM



## INDUSTRIAL | FLOODLIGHT

# TOTT 2 IP65 INTEGRATED LED FLOODLIGHT

9.5-85W | 4000K | 1050-10600lm | 50,000hrs |



**Photometric data:**  
Please refer to our  
website for up to  
date photometric  
information.



**SLIM & EXTRA LIGHTWEIGHT**

**NOT PRE-FIXED**

**RUST FREE HOUSING**


### New PERFORMA TOTT 2

is a non pre-flexed slim, lightweight and integrated LED Floodlight range. Providing high lumen output, powerful and uniform floodlight illumination, that's perfect for numerous applications in the harshest environments.



See page 64 for MEGAMAN® **ESSENTIALS LED FLOODLIGHT (VOSS)** economy option.

### DIMENSIONS



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (L x W x H mm)
<b>710889</b>	9.5W	4000K / 80	1050	N	100°	50,000	180	60x105x132
<b>710890</b>	24W	4000K / 80	2660	N	100°	50,000	390	79x197x179
<b>710891</b>	45W	4000K / 80	5000	N	100°	50,000	550	79x197x230
<b>710677</b>	85W	4000K / 80	10600	N	100°	50,000	1450	84x297x326

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## BULKHEAD | INDOOR

# RENZO

**INNOVATIVE  
PLUG-AND-PLAY  
MODULAR SYSTEM  
DESIGN IN THREE  
DIFFERENT SIZES  
WITH UNIQUE  
MEGAMAN® LIGHTING  
CONTROL OPTIONS.**

### FEATURES & BENEFITS

- Plug-and-play modular design enhances the installation flexibility
- 50,000 hours rated life
- IP44 rated
- Able to mix colour temperature through driver
- High power factor >0.9
- MEGAMAN® RENZO with microwave motion sensor can serve as a master device to control others
- Homogeneous light output with durable PMMA cover avoiding yellowing deterioration
- Suitable for wall and ceiling mounting
- Will not yellow with use
- Part L compliant
- Selectable lumen output (930/1400lm) for RENZO M and (930-2000lm) for RENZO L size
- BESA box mountable

### ACCESSORIES



**710286**  
Microwave  
Motion Sensor



**710267**  
Emergency Kit



3 Year Warranty on  
both Microwave  
Motion Sensor and  
Emergency Kit.



**710264**  
RENZO S

**710430**  
RENZO M

**710274**  
RENZO L

### RENZO MODULAR SYSTEM



CCT Technology Module  
Standard on all 3 sizes in the  
Renzo range



Emergency Kit Module



Microwave Motion Sensor  
Module



LED FIXTURES WITH  
INNOVATIVE ADDED  
VALUE FEATURES

## BULKHEAD | INDOOR

# RENZO INTEGRATED MODULAR LED BULKHEAD

11-22W | 3000K/4000K | 930-2000lm | 50,000hrs | Non-Dim Driver



**PLUG & PLAY MODULAR DESIGN**

**FLICKER FREE**

**TOOLLESS & FAST INSTAL**




**Photometric data:**  
 Please refer to our website for up to date photometric information.



**MEGAMAN® RENZO** consists of 3 unique MEGAMAN® luminaire design elements; Modular System, Switching CCT and Selectable lumen output. This together with 3 different sizes, provides a unique '1 Box' Plug-and-play modular system solution that enables wholesalers and installers, in-situ installation solutions according to their needs. Such as microwave motion sensor and emergency kit.

### DIMENSIONS



See page 68 for MEGAMAN® ESSENTIALS INDOOR LED BULKHEAD (KATIA) economy option.

Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (Dia x D mm)
<b>710264 DUAL CCT*</b>	11W	3000K / 80 4000K / 80	930 1000	N	110°	50,000	420	280x100
<b>710430 DUAL CCT &amp; DUAL OUTPUT</b>	10W	3000K / 80 4000K / 80	930 1000	N	110°	50,000	530	330x110
	15W	3000K / 80 4000K / 80	1300 1400					
<b>710274 DUAL CCT &amp; TRI-LUMEN OUTPUT</b>	10W	3000K / 80 4000K / 80	930 1000	N	110°	50,000	720	390x115
	15W	3000K / 80 4000K / 80	1300 1400					
	22W	3000K / 80 4000K / 80	1850 2000					

\*RENZO S can fit either Emergency Kit or Microwave Sensor module.

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## BULKHEAD | OUTDOOR

# FONDA

**PLUG-AND-PLAY MODULAR IP66 & IK10 LED BULKHEAD. DESIGNED TO PERFORM EFFECTIVELY AND EFFICIENTLY IN THE MOST DEMANDING ENVIRONMENTS.**



### ACCESSORIES



710438 Fonda Eyelid Trim Black



710437 Fonda Eyelid Trim White



710286 Microwave Motion Sensor



710354 Emergency Kit

#### Applications

- Residential/Commercial lighting
- Hotels
- Kitchens
- Corridors and stairwells
- Bathrooms (IP66)

### FEATURES & BENEFITS

- Plug-and-play modular design enhances the installation flexibility
- IK10 vandal resistant rating
- Comes complete with security screws and key
- Corrosion free tough polycarbonate enclosure, UV resistant
- White and black options
- 50,000 hours rated life
- Soft diffused light with low glare and no unsightly hot spots
- MEGAMAN® Fonda Microwave Motion Sensor Module can be used as a master to standard versions (with loop through wiring) to create a more cost-effective way of installing.
- Suitable for numerous indoor and outdoor area applications
- Suitable for wall and ceiling mounting
- Simple and quick toolless push to fit wiring for cost saving install and maintenance
- BESA box mountable

CALL: 01707 386000  
 EMAIL: SALES@MEGAMANUK.COM

## BULKHEAD | OUTDOOR

# FONDA IP66 INTEGRATED MODULAR LED BULKHEAD

10-14W | 4000K | 900lm | IK10 | 50,000hrs |



**PLUG & PLAY MODULAR DESIGN**

**IK10 VANDAL RESISTANT**

**SIMPLE TOOLLESS PUSH FIT WIRING**




Photometric data:  
Please refer to our  
website for up to  
date photometric  
information.



A stylish corrosion free integrated outdoor LED bulkhead with low glare diffuser, **MEGAMAN® FONDA Modular LED Bulkhead**, is a robust modular system designed to provide a flexible lighting solution; that can be easily adapted on site to meet a wide range of outdoor applications. Quick to install with toolless push to fit wiring.

### DIMENSIONS



See page 70 for MEGAMAN® **ESSENTIALS OUTDOOR LED BULKHEAD (RONDA)** economy option.

Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxWxD mm)
<b>710298</b> (WHITE)	10W	4000K / 80	900	N	110°	50,000	820	300x85
<b>710325</b> (BLACK)	10W	4000K / 80	900	N	110°	50,000	820	300x85
<b>710297</b> WITH SENSOR (WHITE)	11W	4000K / 80	900	N	110°	50,000	865	300x85
<b>710327</b> WITH SENSOR (BLACK)	11W	4000K / 80	900	N	110°	50,000	865	300x85
<b>710386</b> EMERGENCY (WHITE)	14W	4000K / 80	900	N	110°	50,000	1050	300x85
<b>710387</b> EMERGENCY (BLACK)	14W	4000K / 80	900	N	110°	50,000	1050	300x85

## BATTEN | INDOOR

# TONO

**A COST-EFFECTIVE AND RELIABLE HIGH PERFORMANCE LED BATTEN THAT IS A TRUE ENERGY EFFICIENT & LONGER OPERATING LIFE REPLACEMENT FOR TRADITIONAL T5 & T8 FLUORESCENT TUBES.**



**Photometric data:**  
 Please refer to our website for up to date photometric information.

### FEATURES & BENEFITS

- Integrated LED Batten
- Integrated driver
- Concealed clip system
- 110° beam angle
- 50,000 hours rated life (L70 B50 at Ta25°C)
- Flicker free (flicker Ratio <3% @100Hz)
- BESA box compatible
- Pre-wired from one end with a 500mm flylead
- Ideal alternative to T5 and T8 fluorescent fitting
- Perfect for a number of different applications
- Simple installation and easy maintenance
- Mounting is quick and tidy
- Wide light distribution
- Reduced maintenance costs
- Highly competitively priced LED batten

**PRE-WIRED**  
 FROM ONE END  
 WITH 500MM  
 FLYLEAD

### Applications

- Residential lighting
- Under cabinet lighting
- Staircases
- Corridors



UK BESA box compatible



LED FIXTURES WITH  
 INNOVATIVE ADDED  
 VALUE FEATURES



## BATTEN | INDOOR

# TONO INTEGRATED LED BATTEN

20-62W | 3000K-6500K | 2050-6550lm | 50,000hrs |




**5YR**  
WARRANTY

**SLIM DESIGN**

**QUICK & EASY INSTALLATION**

**WIDE LIGHT DISTRIBUTION**

### DIMENSIONS



**MEGAMAN® PERFORMA TONO** is a cost-effective and reliable indoor LED batten that is a true replacement for T5 and T8 fluorescent tubes. A highly flexible and energy efficient LED fixture compared to traditional battens; that offers a longer lifetime and significantly lower operational costs. Ensuring a payback that meets the needs of the specification market.

Order Code		Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxW xH mm)
<b>180380</b>	<b>2ft</b>	21W	3000K / 80	2050	N	110°	50,000	225	600x75x24mm
<b>180342E</b>	<b>2ft</b>	20W	4000K / 80	2200	N	110°	50,000	225	600x75x24mm
<b>180390</b>	<b>2ft</b>	21W	6500K / 80	2200	N	110°	50,000	225	600x75x24mm
<b>180382</b>	<b>3ft</b>	31W	3000K / 80	3050	N	110°	50,000	310	900x75x24mm
<b>180344</b>	<b>3ft</b>	31W	4000K / 80	3300	N	110°	50,000	310	900x75x24mm
<b>180392</b>	<b>3ft</b>	31W	6500K / 80	3300	N	110°	50,000	310	900x75x24mm
<b>180384</b>	<b>4ft</b>	42W	3000K / 80	4050	N	110°	50,000	385	1200x75x24mm
<b>180346E</b>	<b>4ft</b>	38W	4000K / 80	4350	N	110°	50,000	385	1200x75x24mm
<b>180394E</b>	<b>4ft</b>	38W	6500K / 80	4350	N	110°	50,000	385	1200x75x24mm
<b>180386E</b>	<b>5ft</b>	48W	3000K / 80	5200	N	110°	50,000	475	1500x75x24mm
<b>180348E</b>	<b>5ft</b>	48W	4000K / 80	5600	N	110°	50,000	475	1500x75x24mm
<b>180396</b>	<b>5ft</b>	52W	6500K / 80	5600	N	110°	50,000	475	1500x75x24mm
<b>180388</b>	<b>6ft</b>	62W	3000K / 80	6100	N	110°	50,000	575	1800x75x24mm
<b>180350</b>	<b>6ft</b>	62W	4000K / 80	6550	N	110°	50,000	575	1800x75x24mm
<b>180398</b>	<b>6ft</b>	62W	6500K / 80	6550	N	110°	50,000	575	1800x75x24mm

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## BATTEN | INDOOR

# FARRON

**MEGAMAN® PERFORMA  
 FARRON INTEGRATED LED  
 BATTEN WITH SINGLE AND  
 TWIN OUTPUT OPTIONS FOR  
 GREATER LIGHTING CONTROL  
 WITH SIGNIFICANT ENERGY  
 AND MAINTENANCE SAVING.**

**BESA BOX  
 COMPATIBLE**

### FEATURES & BENEFITS

- Integrated LED batten with single and twin output options
- Variable and selectable wattages and lumen output
- BESA box compatible
- Optional built-in Microwave Motion Sensor and 3 hour Emergency Kit option available
- 120° beam angle
- 50,000 hours rated life
- High lumen output of up to 6400lm
- Emergency test at the end of batten for ease of use in situ
- Direct 1 to 1 replacement of T5 & T8 conventional linear fluorescent battens
- Easy installation with ability to connect both ends by 25mm conduit and 25mm knockout holes
- Permanent live to facilitate the use of a non-maintained emergency luminaire and sensor modules
- Option to conceal cable entry
- Cable entries and through wiring allows for linear series connection
- Control lighting when not in use
- Wide and even light distribution
- Low flicker ≤8%

#### Standard Version



#### Emergency Version



#### Applications

- Residential lighting
- Commercial lighting
- Public areas
- Schools and universities
- Warehouses
- Corridors

**CALL:** 01707 386000  
**EMAIL:** SALES@MEGAMANUK.COM

## BATTEN | INDOOR

# FARRON INTEGRATED LED BATTEN with optional built-in Microwave Motion Sensor

10-52W | 4000K | 1000-6400lm | 50,000hrs | Single & Twin Output



Photometric data:  
Please refer to our  
website for up to  
date photometric  
information.

**SELECTABLE WATTAGE**

**QUICK & EASY** INSTALLATION & WIRING

**EASY TO USE** EMERGENCY OPTION

**MEGAMAN® PERFORMA LED batten FARRON**, is direct replacement for conventional indoor battens that offers both single and twin output options in one box. FARRON offers substantial energy and maintenance savings through variable and selectable wattages and lumen output. Built-in microwave motion sensor and 3 hour emergency kit options.

## DIMENSIONS



See page 72 for MEGAMAN® ESSENTIALS INDOOR LED BATTEN (GARRON) economy option.

Order Code		Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxWxH mm)
<b>180360</b>	<b>2ft</b>	10/21W	4000K / 80	1000/2100	N	120°	50,000	950	600x80x65
<b>180362</b>	<b>4ft</b>	20/40W	4000K / 80	2000/4000	N	120°	50,000	1720	1200x80x65
<b>180364</b>	<b>5ft</b>	22/52W	4000K / 80	2600/5200	N	120°	50,000	2270	1500x80x65
<b>180372 SENSOR</b>	<b>5ft</b>	22/52W	4000K / 80	2600/5200	N	120°	50,000	2270	1500x80x65
<b>180368 EMERGENCY</b>	<b>5ft</b>	22/52W	4000K / 80	2600/5200	N	120°	50,000	2270	1500x80x65
<b>180376 EMERGENCY &amp; SENSOR</b>	<b>5ft</b>	22/52W	4000K / 80	2600/5200	N	120°	50,000	2270	1500x80x65
<b>180366</b>	<b>6ft</b>	26/52W	4000K / 80	3400/6400	N	120°	50,000	2660	1800x80x65
<b>180374 SENSOR</b>	<b>6ft</b>	26/52W	4000K / 80	3400/6400	N	120°	50,000	2660	1800x80x65
<b>180370 EMERGENCY</b>	<b>6ft</b>	26/52W	4000K / 80	3400/6400	N	120°	50,000	2660	1800x80x65
<b>180378 EMERGENCY &amp; SENSOR</b>	<b>6ft</b>	26/52W	4000K / 80	3400/6400	N	120°	50,000	2660	1800x80x65

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## BATTEN | INDOOR & OUTDOOR

# DINO 2

**MEGAMAN® PERFORMA**  
**DINO 2 IS A TOUGH IP66**  
**WATERPROOF & IK08**  
**VANDAL PROOF BATTEN**  
**IDEAL FOR BOTH OUTDOOR**  
**AND INDOOR APPLICATIONS.**

### Permanent Live Option



L1: Permanent Live  
 L2: Switched Live

4-wire connection, allows unswitched live supply to the luminaire or appliances (i.e. CCTV, security alarm system, smoke detector, etc.) when the switch is off

### ACCESSORIES



DINO 2 PIR sensor enables a master and slave light system

### Applications

- Car Parks
- Warehouses
- Workshops
- Underground areas
- Outdoor areas

### FEATURES & BENEFITS

- Integrated LED batten
- Available in a range of sizes and wattages
- Permanent live option
- Optional cable gland covers available
- PIR Sensor Module available
- 120° beam angle
- 50000 hours rated life (L70 B50 at Ta 25°C)
- High lumen output of up to 6500lm
- Up to 123lm/W
- Offering 4-pole option
- Ideal alternative to T5 and T8 linear outdoor fluorescent luminaires
- Perfect for a number of different applications and spaces
- Simple installation and easy maintenance
- Permanent live to facilitate the use of a non-maintained emergency luminaire and sensor modules
- Option to conceal cable entry
- Cable entries and through wiring allows for linear series connection
- Control lighting when not in use
- Wide and even light distribution
- Reduced maintenance costs



190800 DINO 2  
PIR Sensor



711102 DINO 2  
Emergency Kit



190750 DINO 2  
End Covers



190740 DINO 2  
Suspension Clips



190742 DINO 2  
Brackets for theft protection



LED FIXTURES WITH  
 INNOVATIVE ADDED  
 VALUE FEATURES

## BATTEN | INDOOR & OUTDOOR

# DINO 2 IP66 ANTI-CORROSIVE INTEGRATED LED BATTEN with PIR Sensor & Emergency Kit options

19-53W | 4000K | 1800-6500lm | 50,000hrs |



**ANTI-CORROSIVE IP66 LINEAR BATTEN**

**SUPERIOR REPLACEMENT FOR T5 & T8 BATTENS**

**RANGE OF SIZES & WATTAGES**

**MEGAMAN® PERFORMA DINO 2** is designed to offer an ideal alternative to T5 and T8 waterproof battens for outdoor and indoor applications. It comes with sliding stainless steel clips for easy and flexible installation. The permanent live option of MEGAMAN® DINO 2 allows unswitched live supply to the luminaire or appliances (i.e. sensors, emergency lighting, CCTV, security alarm system, smoke detector and so on.) when the switch is off.

PIR sensor and emergency lighting options are available.




See page 74 for MEGAMAN® ESSENTIALS OUTDOOR LED BATTEN (RUCCA) economy option.



**Photometric data:**  
Please refer to our website for up to date photometric information.

### DIMENSIONS



#### Max. number of connections

- 65 units for 191000
- 59 units for 191002
- 34 units for 191004
- 39 units for 191006
- 23 units for 191008

\* Based on using 1.5mm² wire  
\* Number of looping up to 6A Max.

Order Code		Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxWxH mm)
<b>191000</b>	<b>2.3ft</b>	19W	4000K / 80	1800	N	120°	50,000	679	723x60x54
<b>191002</b>	<b>4.3ft</b>	21W	4000K / 80	2350	N	120°	50,000	1194	1323x60x54
<b>191004</b>	<b>4.3ft</b>	36W	4000K / 80	4300	N	120°	50,000	1571	1323x60x54
<b>191006</b>	<b>5.3ft</b>	32W	4000K / 80	3600	N	120°	50,000	1307	1623x60x54
<b>191008</b>	<b>5.3ft</b>	53W	4000K / 80	6500	N	120°	50,000	1627	1623x60x54

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## BATTEN | CHEMICAL RESISTANT

# DINO 2 FARM

## MEGAMAN® PERFORMA

**DINO 2 FARM IS SPECIFICALLY DESIGNED TO WITHSTAND THE HARSH ENVIRONMENTS FOUND IN MODERN INTENSIVE FARMING.**

### Permanent Live Option



L1: Permanent Live  
 L2: Switched Live

4-wire connection, allows unswitched live supply to the luminaire or appliances (i.e. CCTV, security alarm system, smoke detector, etc.) when the switch is off.

### FEATURES & BENEFITS

- Integrated LED batten
- Permanent live option
- Chemical resistant housing
- PIR Sensor Module available
- IP66 and IK04 high impact resistance rated
- 50000 hours rated life (L80 B10 at Ta 25°C)
- High lumen output of up to 6500lm
- Energy saving efficacies of up to 123lm/W
- Offering 4-pole option
- Ideal low energy alternative to T5 and T8 linear fluorescent luminaires
- Ammonia resistant, making it perfect for the demanding and often harsh farm environments
- Simple fast-fix stainless steel mounting clips for easy installation
- Permanent live to facilitate the use of a non-maintained emergency luminaire and sensor modules
- Option to conceal cable entry
- Control lighting when not in use
- Wide and even light distribution
- Reduced maintenance costs

### ACCESSORIES



DINO 2 PIR sensor enables a master and slave light system



190800 DINO 2  
PIR Sensor



190750 DINO 2  
End Covers



190740 DINO 2  
Suspension Clips



190742 DINO 2  
Brackets for theft  
protection

### Applications

- Agricultural environments
- Livestock husbandry; poultry, cattle and pigs
- Workshops
- Greenhouses
- Outdoor areas

CALL: 01707 386000  
 EMAIL: SALES@MEGAMANUK.COM



## BATTEN | CHEMICAL RESISTANT

# DINO 2 FARM IP66 ANTI-CORROSIVE INTEGRATED LED BATTEN with PIR Sensor option

35-53W | 4000K | 4300-6500lm | 50,000hrs |



**ANTI-CORROSIVE IP66 LINEAR BATTEN**

**CHEMICAL & AMMONIA RESISTANT HOUSING**

**PERMANENT LIVE OPTION**

LEDs need special protection from the aggressive chemical atmospheres in agricultural applications. **MEGAMAN® PERFORMA DINO 2 FARM** is designed to solve the problem in challenging areas such as animal husbandry. The chemical resistant housing materials, and the IP66 and IK04 ratings for ingress protection with high impact resistance enable it to withstand harsh farm environments. Furthermore, the tool-less wiring and fast fixing stainless steel mounting clips enable easy installation.



Photometric data:  
Please refer to our  
website for up to  
date photometric  
information.

### Max. number of connections


- 34 units for 190796
- 23 units for 190798

\* Based on using 1.5mm<sup>2</sup> wire  
\* Number of looping up to 6A Max.



DLG certified with ammonia resistant and is applicable for high pressure cleaning with a minimum distance of 15cm.

### DIMENSIONS



Order Code		Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxWxH mm)
<b>190796</b>	<b>4.3ft</b>	35W	4000K / 80	4300	N	120°	50,000	1060	1323x60x54
<b>190798</b>	<b>5.3ft</b>	53W	4000K / 80	6500	N	120°	50,000	1194	1623x60x54

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## DOWNLIGHT | FULLY FIRE-RATED

# TEGO2

**SIMPLE AND EASY FINGERTIP  
CONTROL OVER BOTH BEAM  
ANGLE & COLOUR TEMPERATURE.  
ALL WITHOUT THE NEED OF  
TOOLS OR REMOVING TEGO 2  
FROM THE CEILING.**



### ACCESSORIES



711085  
TEGO 2  
Chromium  
finish bezel



711087  
TEGO 2  
Brushed Nickel  
finish bezel



711088  
TEGO 2  
Black finish  
bezel

#### Applications

- Retail
- Offices
- Hotels
- Receptions
- Corridors
- Restaurants
- Bathrooms
- Kitchens

### FEATURES & BENEFITS

- TEGO 2 Selectable Dual CCT (2800K or 4000K) is easily activated by a simple twist of the lens once the fixture is installed.
- Press lens front cover to change beam angle with MEGAMAN® Dual Beam Technology
- Toolless wiring block and push-in terminal ensure easy install
- Flexible Loop in/Loop out feature enables for quick connection
- Range of magnetised bezel cover accessories available in 3 design finishes (Black, Chrome & Brushed Nickel)
- IP65 rated
- Flicker free  $\leq 3\%$
- 7.5W with a 650lm output
- Triac Dimming
- 50,000 hour rated life
- Change colour temperature & beam angle with simple fingertip control of lens front cover, with TEGO 2 still in the ceiling
- Versatile range of interchangeable bezel covers available. Easily changed with fixture still in the ceiling, by clicking onto magnetised bezel ring
- TEGO 2 removes the need to 'make good' a ceiling, as all changes can be made from the front of the fitting - saving both time and money!
- Aluminium thermal insulation guard included in box



**NO TOOLS.  
NO MESS.**  
REMOVES CEILING  
'MAKE GOOD'  
WORRIES FOR  
CONTRACTORS



LED FIXTURES WITH  
INNOVATIVE ADDED  
VALUE FEATURES

**MEGAMAN®**  
**Performa**  
FIXTURE RANGE  
HIGH PERFORMANCE & QUALITY FROM MEGAMAN®

## DOWNLIGHT | FULLY FIRE-RATED

# TEGO 2 INTEGRATED FULLY FIRE-RATED LED DOWNLIGHT with Dual Beam Technology (DBT) and Selectable Dual CCT

7.5W | IP65 | 2800K or 4000K | 650lm | 50,000hrs | Dimmable |



**SELECTABLE DUAL CCT 2800 or 4000K**

**2 BEAM ANGLES IN ONE FIXTURE**

**FULLY FIRE-RATED 30/60/90 MINUTE**

**SIMPLE TOOLLESS WIRING**



**New MEGAMAN® TEGO 2** complies to BS476 Part 21 and is designed to withstand fire for up to 30, 60 and 90 minutes. With Megaman's innovative Dual Beam Technology (DBT), TEGO 2 has two beam angles - 60° and 36° - available by simply pressing the lens front cover. Dual CCT 2800K & 4000K can also be activated by a simple twist of the integrated LED lamp lens cover.

Dimmable and IP65 rated with a lumen output of 650lm at 7.5W, the TEGO 2 integrated downlight is ideal for environments with higher moisture, such as bathrooms and kitchens.



See page 76 for MEGAMAN® ESSENTIALS FIRE-RATED LED DOWNLIGHT (TEGO SLIM) economy option.

### DIMENSIONS



Loop through wiring adaptor

Order Code	Watts	Dual CCT Colour Temp (K) / CRI	Lumens (lm)	IP Rating (IP)	Colour/ Finish	Dimmable	Hrs Lamp Life (max)	Dimensions (HxD mm)	Hole Cut-Out (mm)	Beam Angle (DBT)
<b>711183</b>	7.5W	2800 or 4000 / 80 Switchable	650	IP65	Matt White	Y	50,000	72x90	68	36° or 60°

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## DOWNLIGHT | FIRE-RATED

# TEGO

**MEGAMAN® PERFORMA TEGO**  
**IS AN IP65 HIGHLY ENERGY**  
**EFFICIENT FIRE-RATED**  
**DOWNLIGHT THAT OFFERS**  
**EASY INSTAL AND THE**  
**BENEFITS OF BETTER STOCK**  
**MANAGEMENT**

**TILT**  
**ADJUSTABLE**  
WITH A RANGE OF  
INTERCHANGEABLE  
CONTEMPORARY  
FINISH BEZELS

Up to  
84  
lm/W



### FEATURES & BENEFITS

- TEGO enables easy switch to 3000K or 4000K colour temperature with unique Colour Changing Technology (CCT)
- Toolless wiring block and push-in terminal ensure easy install
- Flexible Loop in/Loop out feature enables for quick connection
- Triac Dimmable as standard
- Range of bezel accessories available in 3 design finishes (White, Chrome & Brushed Nickel)
- IP65 rated on fixed versions
- 4 Year warranty
- Fully fire-rated for 30/60/90 minute ceilings
- 5W version has ability to be tilt adjustable with tilt bezel accessories
- Versatile range of interchangeable bezels allows for multitude of finishes with minimal stock lines and space

### ACCESSORIES



**519036 TEGO**  
**FIXED** Chromium  
finish bezel

**519040 TEGO**  
**ADJUSTABLE**  
Chromium  
finish bezel



**519038 TEGO**  
**FIXED** Brushed  
Nickel finish bezel

**519042 TEGO**  
**ADJUSTABLE**  
Brushed Nickel  
finish bezel

**519034 TEGO ADJUSTABLE White**



### PERFORMA TEMPUS®

TEGO Compatible  
Emergency Pack  
EMC Compliant

EMG147247



Designed specifically for  
MEGAMAN® LEDs  
See page: XX

### Applications

- Retail
- Offices
- Hotels
- Receptions
- Corridors
- Restaurants
- Bathrooms
- Kitchens

**CALL:** 01707 386000  
**EMAIL:** SALES@MEGAMANUK.COM

## DOWNLIGHT | FIRE-RATED

# TEGO INTEGRATED FULLY FIRE-RATED LED DOWNLIGHT with Selectable Dual CCT

5W | IP65 | 3000K or 4000K | 420lm | 50,000hrs | Dimmable |



**SELECTABLE DUAL CCT 3000 or 4000K**

**FULLY FIRE-RATED 30/60/90 MINUTE**



**SIMPLE TOOLLESS WIRING**

**PERFORMA TEGO by MEGAMAN®** is a fully integrated fire-rated highly energy efficient LED downlight, featuring our impressive Colour Changing Technology (CCT), which allows for switching to either 3000K warm white or 4000K cool white colour temperature. Triac Dimmable as standard and IP65 rated on all fixed versions. This flexible Loop in/ Loop out easy to install downlight is supplied fixed as standard; with the 5W version having the ability to be tilt adjustable. There is a range of interchangeable different finish fixed and tilt bezel accessories available.



**Photometric data:**  
Please refer to our website for up to date photometric information.

### DIMENSIONS



Loop through wiring adaptor



See page 76 for MEGAMAN® ESSENTIALS FIRE-RATED LED DOWNLIGHT (TEGO SLIM) economy option.

Order Code	Watts	Dual CCT Colour Temp (K) / CRI	Lumens (lm)	IP Rating (IP)	Colour/ Finish	Dimmable	Hrs Lamp Life (max)	Dimensions (HxD mm)	Hole Cut-Out (mm)	Beam Angle (DBT)
<b>519030</b>	5W *With tilt bezel	3000 or 4000 / 80 Switchable	400 (3000K) 420 (4000K)	IP65 IP20*	Matt White	Y	30,000	70x85	73	36°

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

## DOWNLIGHT | RECESSED

# MILENA

**MEGAMAN® PERFORMA**  
**MILENA IS A COST EFFECTIVE**  
**AND IDEAL QUICK & EASY**  
**RETROFIT REPLACEMENT FOR**  
**TRADITIONAL PL COMMERCIAL**  
**DOWNLIGHT INSTALLATIONS**



**MILENA**  
**DOWNLIGHTS**  
 IDEAL RETROFIT  
 FOR EXISTING  
 INSTALLATIONS  
 & THEIR  
 CUT-OUTS

#### Applications

- Retail
- Offices
- Hotels
- Receptions
- Restaurants
- Bathrooms
- Kitchens

#### FEATURES & BENEFITS

- Recessed integrated LED downlight
- Downlight unit consists of dual-lumen output & dual-CCT LED light engine
- Switchable CCT of warm 3000K or cool 4000K light
- Built-in driver
- IP54
- 50,000 hours rated life (L80 B10 at Ta 25°C)
- Flicker free ≤3%
- The modular components design allows toolless assembly in-situ
- Flexible design enables a faster delivery period for customised requirements, which is an ideal solution for short lead time projects
- Total control and flexibility from Milena modular downlight system is ideal for retrofit in existing conventional installations and their ceiling cut-outs
- Toolless install allows for quick install and maintenance
- Wide and uniform light distribution



MILENA's modular design allows quick and easy install and maintenance



LED FIXTURES WITH  
 INNOVATIVE ADDED  
 VALUE FEATURES

## DOWNLIGHT | RECESSED

# MILENA INTEGRATED LED DOWNLIGHT with Selectable Dual CCT and Dual Lumen Output

6.5-25W | IP54 | 3000K or 4000K | 600-27000lm | 50,000hrs |



4"  
6.5/9W  
710409



**Photometric data:**  
Please refer to our website for up to date photometric information.

**SELECTABLE DUAL CCT** 3000 or 4000K

**SIMPLE TOOLLESS** MODULAR ASSEMBLY

**DUAL LUMEN** OUTPUT UP TO 2700LM

**MEGAMAN® MILENA** is a compact modular downlight unit consisting of dual-lumen output & dual-CCT LED light engine and is perfect for use directly under thermal insulated ceiling recesses.




The luminaire offers maximum visual comfort by high cut-off angle for better glare control and low flicker to avoid eye fatigue.



**BRINGING YOU MORE CHOICE!**

See page 78 for MEGAMAN® **ESSENTIALS LED DOWNLIGHT (MILENALITE)** economy option.

### DIMENSIONS



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	IP Rating (IP)	Colour/ Finish	Hrs Lamp Life (max)	Dimensions (H x Dia mm)	Hole Cut-Out (mm)	Beam Angle
<b>710709</b>	6.5/9W	3000K or 4000K / 80 Switchable	600/830 (3000K) 650/900 (4000K)	IP54	Matt White	50,000	87x130	100	100°
<b>710689</b>	18/23W	3000K or 4000K / 80 Switchable	1670/2230 (3000K) 1800/2400 (4000K)	IP54	Matt White	50,000	87x172	150	100°
<b>710691</b>	19.5/25W	3000K or 4000K / 80 Switchable	1860/2500 (3000K) 2000/2700 (4000K)	IP54	Matt White	50,000	97x225	200	100°

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C



## SPECIAL ORDERS | NEW FIXTURES

BY ORDER  
ONLY



### EKON IP66 OUTDOOR STADIUM INTEGRATED LED FLOODLIGHT

MEGAMAN® PERFORMA EKON is a high lumen stadium floodlight that delivers exceptional lighting performance up to 17500lm with 140lm/W efficiency. EKON offers symmetric & asymmetric options for uniform light, which deliver a highly focused light beams with low glare and enhanced photometric control.

**NEW**

For further details please call MEGAMAN® sales on 01707 386000 or your local MEGAMAN® BDM

**5YR**  
WARRANTY

MEGAMAN®  
**Performa**  
 FIXTURE RANGE  
 HIGH PERFORMANCE & QUALITY FROM MEGAMAN®

MEGAMAN® PERFORMA | SPECIAL ORDERS

BY ORDER  
ONLY

### TITO IP66 OUTDOOR INTEGRATED LED FLOODLIGHT



MEGAMAN® PERFORMA TITO is a dedicated LED floodlight that is highly energy efficient; with up to 60% energy saving delivered throughout the 4 different size floodlight range. TITO has a slim and robust corrosion resistant aluminium housing, together with IP66 & IK08 rating. Making this truly versatile and cost effect replacement for discharge lamp floodlights.

**NEW**

For further details please call MEGAMAN® sales on 01707 386000 or your local MEGAMAN® BDM



**5YR**  
WARRANTY

MEGAMAN®  
**Performa**  
 FIXTURE RANGE  
 HIGH PERFORMANCE & QUALITY FROM MEGAMAN®

## SPECIAL ORDERS | NEW FIXTURES

BY ORDER  
ONLY

### ESTELA 2 INTEGRATED LED LOUVRE PANEL

NEW

MEGAMAN® PERFORMA ESTELA 2 is a contemporary design LED louvre panel that provides a high quality and flicker free uniform light, that is ideal for hard working office environments.

For further details please call MEGAMAN® sales on 01707 386000 or your local MEGAMAN® BDM

5YR  
WARRANTY

MEGAMAN®  
**Performa**  
 FIXTURE RANGE  
 HIGH PERFORMANCE & QUALITY FROM MEGAMAN®

BY ORDER  
ONLY

### XAVIER INTEGRATED LED TRACK PANEL

NEW

MEGAMAN® PERFORMA XAVIER is a complete LED Track system especially designed to deliver a perfect and uniform distribution of light; that is ideal for shop and retail applications.

For further details please call MEGAMAN® sales on 01707 386000 or your local MEGAMAN® BDM

5YR  
WARRANTY

MEGAMAN®  
**Performa**  
 FIXTURE RANGE  
 HIGH PERFORMANCE & QUALITY FROM MEGAMAN®

# TRACK LIGHTING



High performance and innovative integrated LED track downlights from the MEGAMAN® PERFORMA fixture range.

## PERFORMA TRACK LIGHTING | LED TRACK LIGHT



MARCO MINI TRACK LIGHT P34



MARCO MIDI DUAL BEAM TRACK LIGHT P36



MARCO TRACK LIGHT P38



3-CIRCUIT TRACK SYSTEM P38

MEGAMAN®'s highly energy efficient and stylish **TRACK LIGHT FIXTURES** provide ideal replacements for conventional halogen and metal halide applications; whilst offering superior and often a more versatile lighting solutions, as demonstrated in the highly flexible and innovative Dual Beam Technology (DBT) found in our MARCO Midi integrated LED track light. This advanced LED beam shaping technology enables the Megaman MARCO track lights to have two beam angles (25°/45°) to choose from, making it ideal for a host of demanding retail and commercial applications.

Find out what you can achieve by specifying Megaman's latest high quality LED lighting technology in or with our integrated and non-integrated track light fixtures and using them to their maximum effect!



## TRACK LIGHTING | INTEGRATED LED

# MARCO MINI

**MEGAMAN® PERFORMA MARCO MINI** IS A CLASSIC UNDERSTATED DESIGN INTEGRATED LED TRACK LIGHT, THAT OFFERS HIGH COLOUR RENDERING AND ENERGY EFFICIENCY.

### FEATURES & BENEFITS

- Compact LED track light with an understated classic design and concealed driver
- Replacement for 75W halogen/20W CDM-Rm
- Excellent colour rendering index of 97 with MEGAMAN® Ultra Rich Colour option
- Very efficient with up to 83lm/W
- Adjustable arm for multi-directional lighting: 330° horizontal rotation and 90° vertical tilting angle
- Easy to understand mechanism, no electrician needed
- High colour consistency SDCM≤3
- White aluminium finish

MULTI  
DIRECTIONAL  
HIGH QUALITY  
AND HIGH  
PERFORMANCE  
LIGHTING

### Applications

- Retail
- Shop lighting
- Hotels
- Receptions
- Restaurants
- Museums
- Galleries



LED FIXTURES WITH  
INNOVATIVE ADDED  
VALUE FEATURES

## TRACK LIGHTING | INTEGRATED LED

# MARCO MINI INTEGRATED LED TRACK LIGHT with Built-in Driver

12W | IP20 | 2800K / 4000K | 950-1000lm | 25,000hrs |



**COMPACT LED** TRACK LIGHT

**IDEAL REPLACEMENT** FOR 75W HALOGEN

**ENERGY EFFICIENT** UP TO 83LM/W




**Photometric data:**  
 Please refer to our  
 website for up to  
 date photometric  
 information.



**MEGAMAN® PERFORMA MARCO MINI**  
 is an understated classic design and  
 built-in driver Integrated LED Track  
 light incorporates Hybrid Reflector  
 Technology which offers commercial  
 users superb colour rendering and  
 beam control, which is essential for all  
 retail environments.

### DIMENSIONS



Order Code	Watts	Colour Temp (K)	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Colour/ Finish	Weight (g)	Dimensions (LxD mm)	Rotation
<b>164004</b>	12W	2800K / 80	950	N	36°	25,000	White	170	160x50	330°
<b>164006</b>	12W	4000K / 80	1000	N	36°	25,000	White	170	160x50	330°



## TRACK LIGHTING | INTEGRATED LED

# MARCO MIDI

**MEGAMAN® PERFORMA MARCO MIDI IS AN INNOVATIVE & VERY FLEXIBLE INTEGRATED LED TRACK LIGHT, THAT INCORPORATES MEGAMAN®'S GROUNDBREAKING DUAL BEAM TECHNOLOGY (DBT).**



**MARCO MIDI**  
 WITH INNOVATIVE  
 DUAL BEAM  
 TECHNOLOGY

### DBT



**HOW IT WORKS** - The mechanism that makes Dual Beam illumination possible is cleverly engineered into the DBT enabled luminaire. To shape the beam angle of such luminaire, simply apply a push action on the front lens. This unique mechanism enables users to switch beam angles instantly from a narrow beam to a wide beam and vice versa.

## DUAL BEAM TECHNOLOGY

### FEATURES & BENEFITS

- MEGAMAN®'s groundbreaking Dual Beam Technology (DBT) giving dynamic full control of two beam angles (25°/45°) from a single fixture
- Compact LED track light with a built-in driver
- Replacement for 35W Metal Halide/CDM-Rm
- Excellent colour rendering index of 97 with MEGAMAN® Ultra Rich Colour option
- Very efficient with up to 91.6lm/W
- 50,000 hour rated life at L70, B50 at Ta25°C
- Adjustable arm for multi-directional lighting: 330° horizontal rotation and 90° vertical tilting angle
- High colour consistency SDCM≤3
- Optional accessories of spread/rectangular lens, barn doors and coloured filters are also available for improved glare control
- 2 beam options for a wide range of display applications
- A variety of lighting control accessories are available

### Applications

- Retail
- Shop lighting
- Hotels
- Receptions
- Restaurants
- Museums
- Galleries

**CALL:** 01707 386000  
**EMAIL:** SALES@MEGAMANUK.COM



## TRACK LIGHTING | INTEGRATED LED

# MARCO MIDI INTEGRATED DUAL BEAM LED TRACK LIGHT with Built-in Driver

24W | IP20 | 3000K / 4000K | 2100-2200lm | 50,000hrs |



**COMPACT LED TRACK LIGHT**

**IDEAL REPLACEMENT FOR 75W HALOGEN**

**ENERGY EFFICIENT UP TO 91.6LM/W**




With an understated classic design and built-in driver, the **MEGAMAN® PERFORMA MARCO MIDI** Integrated LED Track light is equipped with MEGAMAN® groundbreaking LED lighting technology – the **Dual Beam Technology (DBT)**, it is dedicated to enhance the flexibility of beam angles in one single luminaire and help to facilitate inventory management.

DBT is an innovative approach for switching the size of the light spot with a finger press on lens. With this technology one can shape the light spot of the lamp / luminaire from a narrow beam angle to a wider beam angle.



**Photometric data:**  
Please refer to our website for up to date photometric information.

### DIMENSIONS



Order Code	Watts	Colour Temp (K)	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Colour/ Finish	Weight (g)	Dimensions (LxD mm)	Rotation
<b>144004</b>	24W	3000K / 80	2100	N	25° / 45°	50,000	White	1225	198x65	330°
<b>144006</b>	24W	4000K / 80	2200	N	25° / 45°	50,000	White	1225	198x65	330°

## TRACK LIGHTING | INTEGRATED LED

# MARCO

**MEGAMAN® PERFORMA MARCO**  
 A HIGH QUALITY AND POWERFUL  
 INTEGRATED LED TRACK  
 DOWNLIGHT, DESIGNED TO  
 ENHANCE TODAY'S DEMANDING  
 RETAIL & DISPLAY ENVIRONMENTS.



### FEATURES & BENEFITS

- Compact LED track light with an understated classic design and concealed driver
- Replacement for 75W halogen/20W CDM-Rm
- Excellent colour rendering index of 97 with MEGAMAN® Ultra Rich Colour option
- Very efficient with up to 96lm/W
- Adjustable arm for multi-directional lighting: 330° horizontal rotation and 90° vertical tilting angle
- Easy to understand mechanism, no electrician needed
- High colour consistency SDCM ≤ 3
- White aluminium finish

## IGNITE THE SPENDING POWER

Retail shopping is exciting and fast-paced and a quality lighting scheme can make a big difference in this setting. It can create a welcoming environment increasing the amount of time customers spend in the shop and increasing the chances of a purchase by bringing colours in products to life. MEGAMAN®'s innovative LED Track Downlights, both integrated and non-integrated, are built with design in mind, they are environmentally friendly, stylish and have zero heat emissions.



LED FIXTURES WITH  
 INNOVATIVE ADDED  
 VALUE FEATURES

## TRACK LIGHTING | INTEGRATED LED

# MARCO INTEGRATED LED TRACK with Built-in Driver


37-52W | IP20 | 4000K | 2100-5000lm | 50,000hrs |



**Photometric data:**  
 Please refer to our website for up to date photometric information.

**MEGAMAN® PERFORMA MARCO**  
 an understated classic design and built-in driver Integrated LED Track light incorporates Hybrid Reflector Technology which offers commercial users superb colour rendering and beam control, which is essential for all retail environments.

### DIMENSIONS



- Applications**
- Retail
  - Shop lighting
  - Hotels
  - Receptions
  - Restaurants
  - Museums
  - Galleries

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Colour/ Finish	Weight (g)	Dimensions (LxD mm)	Rotation
164010	37W	4000K / 80	2100	N	25°	50,000	White	1225	248x110	330°
164014	37W	4000K / 80	2200	N	45°	50,000	White	1225	248x110	330°
164022	52W	4000K / 80	5000	N	45°	50,000	White	1225	248x110	330°

## TRACK LIGHTING | INTEGRATED LED

### ACCESSORIES

Extensive range of accessories allows for versatility and limitless design options, can add or remove track spots easily as required.



Live end connector  
- Right feed  
161011 (WHITE)  
161013 (BLACK)



Live end connector  
- Right feed  
161014 (WHITE)  
161016 (BLACK)



End cap  
161017 (WHITE)  
161019 (BLACK)



Mechanical coupler  
161020 (WHITE)  
161022 (BLACK)



Mechanical insulated  
coupler  
- Left feed  
161023 (WHITE)  
161025 (BLACK)



Straight electrical-  
mechanical coupler  
161026 (WHITE)  
161028 (BLACK)



L-Coupler - Left  
161029 (WHITE)  
161031 (BLACK)



L-Coupler - Right  
161032 (WHITE)  
161034 (BLACK)



T-Coupler left -  
Outside  
161035 (WHITE)  
161037 (BLACK)



T-Coupler left  
- Inside  
161038 (WHITE)  
161040 (BLACK)



T-Coupler right  
- Outside  
161041 (WHITE)  
161043 (BLACK)



T-Coupler right  
- Inside  
161044 (WHITE)  
161046 (BLACK)



X-Coupler  
161047 (WHITE)  
161049 (BLACK)



Flexible coupler  
161050 (WHITE)  
161052 (BLACK)



Ceiling wall mounting  
kit  
161053 (WHITE)  
161055 (BLACK)



Suspension kit  
161053

## TRACK LIGHTING | INTEGRATED LED

# 3-CIRCUIT SYSTEM TRACK



**TOUGH ALUMINIUM** PROFILE

**EXTENSIVE RANGE** OF ACCESSORIES


**SURFACE MOUNTED** OR **SUSPENDED**

**MEGAMAN® PERFORMA 3-CIRCUIT TRACK SYSTEM** is a high quality three circuit display lighting solution with ageless appeal and simple proven functionality and reliability.

### FEATURES & BENEFITS

- 3 circuit surface mounted track, 230V 16A
- Tough aluminium profile in 1m and 2m lengths
- Universal track configuration
- Available in black and white
- Accessories including flexible joints, couplers and connectors sold separately
- 3 circuits allow for multiple scene setting options to create varied effects
- Suitable for wide variety of Megaman track spots  
3800W loading potential across 3 circuits

### DIMENSIONS



Order Code	Colour	Length (m)
<b>161001</b>	White	1m
<b>161003</b>	Black	1m
<b>161004</b>	White	2m
<b>161006</b>	Black	2m

### Applications:

- Retail lighting
- Museums and galleries
- Showrooms
- Exhibitions




# TEMPUS® EMERGENCY SELF-TEST LIGHTING



MEGAMAN® PERFORMA  
TEMPUS® new range of  
high quality maintained  
and non-maintained  
self-test emergency  
lighting solutions.

# TEMPUS® EMERGENCY LIGHTING | SELF-TEST





## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# SLIM BULKHEAD EMERGENCY 3 HOUR MAINTAINED / NON-MAINTAINED

4W | IP65 | 6500K | 140lm | 3 hrs | Self-Test |



**IP65 EMERGENCY BULKHEAD**

**FAST & EASY SURFACE MOUNTED INSTAL**


**3 HOUR EMERGENCY POWER TIME**



### FEATURES & BENEFITS

- 3 hour power time duration
- Included advanced high specification Ni-MH battery
- IP65 dust and weatherproof
- Corrosion resistant, durable polycarbonate housing
- Maintained/Non-maintained operation mode
- Green and red colour status LED indicator
- All direction exit sign stickers included
- Fast & easy surface mounted installation
- Multi-purpose application
- Self-test button located at the bottom of the fixture

### DIMENSIONS



All direction exit sign stickers included



See page 84 for MEGAMAN® ESSENTIALS TEMPUS® EMERGENCY SLIM BULKHEAD economy option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
711052	4W	6500K	140	3.6V 1000mAh Ni-MH	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	610	352x110x67

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# EXIT METAL LIGHT BOX EMERGENCY 3 HOUR MAINTAINED / NON-MAINTAINED

5W | IP20 | 6500K | 35lm | 3hrs | Self-Test |



**MULTI-PURPOSE** APPLICATION


**ANTI-CORROSION** STEEL HOUSING

**3 HOUR EMERGENCY** POWER TIME

### FEATURES & BENEFITS

- 3 hour power time duration
- Included advanced high specification Ni-Cd battery
- Durable steel housing with anti-corrosion powder coating
- Maintained / Non-maintained operation mode
- Integral green and red colour status LED indicator
- Supplied with arrow down legend - other options available
- Light in weight, so easy wall mounting install
- Easy to add all exit direction legend options available
- Multi-purpose application
- Self-test button located at the bottom of the fixture

### DIMENSIONS



### ACCESSORIES

- 710478** Arrow Left Legend  
**710479** Arrow Right Legend  
**710491** Arrow Up Legend



See page 85 for MEGAMAN® ESSENTIALS TEMPUS® EMERGENCY EXIT METAL LIGHT BOX economy option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
<b>711051</b>	5W	6500K	35	3.6V 1800mAh Ni-Cd	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	1330	390x190x62

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# EXIT PLASTIC SIGN EMERGENCY 3 HOUR WALL MOUNTED NON-MAINTAINED

3.5W | IP20 | 6500K | 35lm | 3 hrs | Self-Test |



**ULTRA SLIM PLASTIC** EMERGENCY EXIT SIGN


**FAST & EASY** WALL MOUNTED INSTALLATION

**3 HOUR EMERGENCY** POWER TIME

### FEATURES & BENEFITS

- Wall mounted emergency exit sign
- 3 hour power time duration
- 24 hour charge time
- Included advanced high specification Ni-MH battery
- 850°C glow-wiring test
- Non-maintained operation mode
- Green and red colour status LED indicator
- Polycarbonate construction
- Light in weight for easy install
- Easy mounting 1-side pictogram options available
- Comply with EN60598-1, EN 60598-2-22, UN 38.3 & IEC 62133
- Self-test button located at the bottom of the fixture

### DIMENSIONS



### ACCESSORIES

- 710489** Arrow Left/Right PVC Legend  
**710492** Arrow Up PVC Legend



See page 87 for MEGAMAN® ESSENTIALS TEMPUS® EMERGENCY EXIT PLASTIC SIGN economy option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
<b>711050</b>	3.5W	6500K	35	3.6V 1000mAh Ni-MH	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	1330	316x54x196

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# ULTRA SLIM RECESSED EXIT SIGN EMERGENCY 3 HOUR MAINTAINED

2.6W | 6500K | 35lm | 3 hrs | Self-Test |

CLASS  
II

20  
WEEKS  
DISCOUNT GROUP

PER  
BOX  
1/6

2YR  
WARRANTY

ULTRA SLIM 2 SIDED EMERGENCY EXIT SIGN

6500K ILLUMINATION ACROSS EXIT LEGEND

3 HOUR EMERGENCY POWER TIME


NEW



### FEATURES & BENEFITS

- Recessed emergency exit sign
- 3 hour power time duration
- 24 hour charge time
- Included advanced high specification Ni-MH battery
- 850°C glow-wiring test
- Maintained operation mode
- Green and red colour status LED indicator
- Polycarbonate and aluminium construction:
- Compact and light in weight for easy install
- Comply with EN60598-1, EN 60598-2-22, UN 38 3 & IEC 62133
- Self-test button located at the bottom of the fixture

### DIMENSIONS



Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
711049	2.6W	6500K	35	3.6V 1000mAh Ni-MH	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	610	365x100x238

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# HIGH BAY DOWNLIGHT EMERGENCY SURFACE MOUNTED 3 HOUR NON-MAINTAINED

2W | IP54 | 6000K | 200lm | 3 hrs | Self-Test |



**IP54 SELF-TEST HIGH BAY DOWNLIGHT**


**FAST & EASY SURFACE MOUNTED INSTAL**

**3 HOUR EMERGENCY POWER TIME**

### FEATURES & BENEFITS

- 3 hours emergency duration
- Able to work in high bay areas?
- Non-maintained operation mode
- IP54 Protection
- Compact in size
- Advanced LiFePO4 battery
- Green and red colour status LED indicator
- Touch self-testing button located at the bottom of fixture
- High Bay optics of 30m max height
- Comply with EN 60598-2-22, UN 38.3 and IES 62133
- Overcharge and over-discharge protection, over-temperature protection, short circuit protection

### DIMENSIONS



Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (LxWxH mm)
711365	2W	6000K	200	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	18°	130x130x35

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# LOW BAY DOWNLIGHT EMERGENCY SURFACE MOUNTED 3 HOUR NON-MAINTAINED

2W | IP54 | 6000K | 200lm | 3 hrs | Self-Test |



**IP54 SELF-TEST LOW BAY DOWNLIGHT**


**FAST & EASY SURFACE MOUNTED INSTAL**

**3 HOUR EMERGENCY POWER TIME**

### FEATURES & BENEFITS

- 3 hours emergency duration
- Able to work in high bay areas?
- Non-maintained operation mode
- IP54 Protection
- Compact in size
- Advanced LiFePO4 battery
- Green and red colour status LED indicator
- Touch self-testing button located at the bottom of fixture
- Low Bay optics of 20m max height
- Comply with EN 60598-2-22, UN 38.3 and IES 62133
- Overcharge and over-discharge protection, over-temperature protection, short circuit protection

### DIMENSIONS



Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (LxWxH mm)
711366	2W	6000K	200	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	45°	130x130x35

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# OPEN AREA DOWNLIGHT EMERGENCY SURFACE MOUNTED 3 HOUR NON-MAINTAINED

1W | IP54 | 6000K | 130lm | 3 hrs | Self-Test |



**IP54 SELF-TEST COMPACT DOWNLIGHT**


**FAST & EASY SURFACE MOUNTED INSTAL**

**3 HOUR EMERGENCY POWER TIME**

### FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- IP54 polycarbonate housing
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch self-testing button located at the bottom of fixture
- 850°C glow-wiring test
- 50,000 hours rated life
- Green and red colour status LED indicator
- SELV Constant current output
- Comply with EN 60598-2-22, UN 38.3 & IEC 62133

### DIMENSIONS



See page 90 for MEGAMAN® ESSENTIALS TEMPUS® EMERGENCY OPEN AREA DOWNLIGHT economy option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (LxWxH mm)
711046	1W	6000K	130	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	140°	130x130x35



## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# CORRIDOR DOWNLIGHT EMERGENCY SURFACE MOUNTED 3 HOUR NON-MAINTAINED

1W | IP54 | 6000K | 200lm | 3 hrs | Self-Test |



**IP54 SELF-TEST COMPACT DOWNLIGHT**


**FAST & EASY SURFACE MOUNTED INSTAL**

**3 HOUR EMERGENCY POWER TIME**

### FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- IP54 polycarbonate housing
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch self-testing button located at the bottom of fixture
- 850°C glow-wiring test
- 50,000 hours rated life
- Green and red colour status LED indicator
- SELV Constant current output
- Comply with EN 60598-2-22, UN 38.3 & IEC 62133

### DIMENSIONS



See page 91 for MEGAMAN® ESSENTIALS TEMPUS® EMERGENCY CORRIDOR economy option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (LxWxH mm)
<b>711047</b>	1W	6000K	130	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	140°	130x130x35

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# OPEN AREA DOWNLIGHT EMERGENCY RECESSED 3 HOUR NON-MAINTAINED

1W | IP20 | 6000K | 120lm | 3 hrs | Self-Test |



**IP20 SELF-TEST ULTRA-LOW PROFILE DOWNLIGHT**


**FAST & EASY RECESSED INSTALLATION**

**3 HOUR EMERGENCY POWER TIME**

### FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- IP20 polycarbonate housing
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch self-testing button located at the bottom of fixture
- 850°C glow-wiring test
- 50,000 hours rated life
- Green and red colour status LED indicator
- SELV Constant current output
- Comply with EN 60598-2-22, UN 38.3 & IEC 62133

### DIMENSIONS



ø36mm Hole Cut-out



See page 88 for MEGAMAN® ESSENTIALS TEMPUS®  
 EMERGENCY OPEN AREA DOWNLIGHT economy option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (WxDia mm)
<b>711044</b>	1W	6000K	120	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	140°	23x40

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# CORRIDOR DOWNLIGHT EMERGENCY RECESSED 3 HOUR NON-MAINTAINED

1W | IP20 | 6000K | 120lm | 3 hrs | Self-Test |



**IP20 SELF-TEST ULTRA-LOW PROFILE DOWNLIGHT**


**FAST & EASY RECESSED INSTALLATION**

**3 HOUR EMERGENCY POWER TIME**

### FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- IP20 polycarbonate housing
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch self-testing button located at the bottom of fixture
- 850°C glow-wiring test
- 50,000 hours rated life
- Green and red colour status LED indicator
- SELV Constant current output
- Comply with EN 60598-2-22, UN 38.3 & IEC 62133

### DIMENSIONS



ø36mm Hole Cut-out



See page 89 for MEGAMAN® ESSENTIALS TEMPUS® EMERGENCY CORRIDOR economy option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (WxDia mm)
<b>711045</b>	1W	6000K	120	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	140°	23x40

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



# EMERGENCY KIT FOR LED PANELS

## 3 HOUR EMC COMPLIANT

2.5W | 3 hrs | Self-Test |



**COMPACT SELF-CONTAINED & LIGHTWEIGHT**


**SELV CONSTANT CURRENT OUTPUT**

**3 HOUR EMERGENCY POWER TIME**

### FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch self-testing button and integral status indicator (Flexible for LED module with a forward voltage of 10-90VDC)
- 850°C glow-wiring test
- SELV Constant current output
- Comply with EN 60598-2-22, UN 38.3 & IEC 62133
- Comes with connector for quick and easy plug and play installations

### DIMENSIONS



Order Code	Watts	Battery	Battery Duration	Working Temp.	Rated Supply	Weight	Dimensions (LxWxH mm)
<b>711048</b>	2.5W	6.4V 1500mAh LiFePO4	3 hours	0°C - +40°C	220VAC / 50-60Hz	233	199x55.2x24.5

## TEMPUS® EMERGENCY LIGHTING | SELF-TEST



MEGAMAN® PERFORMA | TEMPUS® EMERGENCY SELF-TEST

# LED FIXTURES

MEGAMAN® ESSENTIALS  
TEMPUS® new range of  
everyday great value for  
money indoor and outdoor  
LED fixtures.

ALL  
ROUND  
BEST VALUE  
&  
CHOICE



# MEGAMAN® ESSENTIALS | LED FIXTURES RANGE




BERTO BACKLIT LED PANEL P60



KATIA INDOOR LED BULKHEAD P68



TEGO SLIM FIRE-RATED DOWNLIGHT P76



KEO LED HIGH BAY P62



RONDA OUTDOOR LED BULKHEAD P70



MILENALITE LED DOWNLIGHT P78



VOSS LED FLOODLIGHT P64



GARRON INDOOR LED BATTEN P72



KANA LED DOWNLIGHT P74



VOSS LED FLOODLIGHT WITH PIR SENSOR P66



ROCCA SINGLE & TWIN INDOOR BATTEN P74






## COMMERCIAL | LED PANEL

# BERTO

GREAT VALUE FOR MONEY **ESSENTIALS**  
**BERTO BACKLIT TPa LED PANELS** DELIVER A FLICKER FREE AND LOW GLARE EVEN LIGHT DISTRIBUTION AND ARE IDEAL FOR LIMITED CEILING ACCESS APPLICATIONS.

### FEATURES & BENEFITS

- High performance Backlit TPa LED  $\leq$ UGR22 panels
- Comes with non dimming driver
- Surface and suspension mounting kits available separately
- 110° beam angle
- 50,000 hours rated life
- Up to 100 lumen per system watt efficacy
- Perfect for shallow ceiling voids
- Quick & easy installation
- Lightweight LED panel with non discolouring TPa rated diffusers
- Flexible installation methods – surface mounted or suspended
- Suitable for use in exposed T-grid ceilings
- 5 Year warranty on panel & driver
- Long maintenance period and low lumen depreciation
- Can be used as part of a Part L building compliance



Loop through wiring adapto

### ACCESSORIES



**710502BACKLIT**  
Emergency Kit for Backlit panels with connectors



**710941**  
DALI Driver  
199x55x24.5mm



**710940**  
Loop Through Junction Box with 3 Pin



**130212**  
Suspension Kit for Panel, 1.8m



**130214**  
Suspension Kit for Panel, 1.0m



**710933** Surface Mounted Ceiling Frame.  
595mmx595mm



## COMMERCIAL | LED PANEL

### BERTO BACKLIT TPα LED PANEL

36W-43W | 4000K/6500K | 3600-4600lm | 50,000hrs |



SQUARE & RECTANGULAR SLIM LED PANELS

EASY PUSH TO FIT CONNECTORS

NON DISCOLOURING TPα DIFFUSERS

TPα  
BACKLIT




Photometric data:  
Please refer to our  
website for up to  
date photometric  
information.

#### MEGAMAN® ESSENTIALS BERTO

**BACKLIT TPα LED Panel** is a integrated lighting solution that facilitates easy installation and maintenance. It delivers a high luminous efficacy up to 110lm/W - matching the lighting levels of 3 x 18W T8 and 3 x 24W HE T5 fluorescent modular fittings.

#### DIMENSIONS



BRINGING YOU  
MORE CHOICE!



See page 6 for MEGAMAN® **PERFORMA BERTO SIDELIT LED PANEL** high quality and performance option.


Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Dimensions (LxWxH mm)
<b>710675</b> UGR22 TPα BACKLIT (SQUARE) X2 PANEL	36W	4000K / 80	3600	N	110°	50,000	595x595x33
<b>710676</b> UGR22 TPα BACKLIT (SQUARE) X2 PANEL	36W	6500K / 80	3600	N	110°	50,000	595x595x33
<b>711081</b> UGR22 TPα BACKLIT (RECTANGULAR) X1 PANEL	43W	4000K / 80	4600	N	110°	50,000	595x1195x33
<b>711082</b> UGR22 TPα BACKLIT (RECTANGULAR) X1 PANEL	43W	6500K / 80	4600	N	110°	50,000	595x1195x33

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C


## INDUSTRIAL | HIGH BAY

### KEO


**MEGAMAN® ESSENTIALS KEO IS AN ALL ROUND GREAT VALUE FOR MONEY ROBUST IP65 RATED MODERN LED HIGH BAY. IDEAL FOR DEMANDING LARGE AREA APPLICATIONS.**



**711260 - 100W**



**711261 - 150W**




**711263 - 200W**

#### FEATURES & BENEFITS

- Replacement for traditional high bay in durable die-cast aluminium with anti-corrosion powder coating
- High luminous efficacy with up to 135lm/W
- Easy installation with single point hook mounting design
- IP65 protection and high vandal resistant with IK08
- 50,000hrs@L70B50 @Ta40°C
- Twist and lock modular micro-wave motion sensor option
- Surface mounted bracket as optional accessory
- Equipped with 100cm length H05RN-F 3\*1.0mm2 power cable
- High surge protection level: 4000V (L-N) ; 6000V (L,N-PE)
- Operation temperature -30 to +50

#### ACCESSORIES



**711264**  
Microwave  
Motion Sensor



**711321**  
100W Surface  
Mounting Bracket



**711322**  
150W Surface  
Mounting Bracket



**711323**  
200W Surface  
Mounting Bracket



**711320**  
Motion Sensor  
Remote Control

#### Applications

- Shopping centres
- Retail stores
- Hospitals
- General lighting

CALL: 01707 386000  
EMAIL: SALES@MEGAMANUK.COM

## INDUSTRIAL | HIGH BAY

### KEO INTEGRATED LED HIGH BAY

100W-200W | IP65 | 4000K | 13500-27000lm | 50,000hrs |



**COST EFFECTIVE IP65 LED HIGH BAY**

**EASY SINGLE POINT INSTALLATION**

**REMOTE CONTROLLER OPTION**






**Photometric data:**  
Please refer to our website for up to date photometric information.

#### MEGAMAN® ESSENTIALS

**INTEGRATED LED HIGH BAY** is a new and cost effective high bay solution with a durable die-cast aluminium housing and anti-corrosion coating. Modular plug and play microwave motion sensor option with standby dimming which is configurable by optional remote controller for energy saving and safety consideration.

#### DIMENSIONS



See page 10 for MEGAMAN® **PERFORMA GEO 2 HIGH BAY** high quality and performance option.

Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Beam Angle	Power Factor (λ)	Hrs Lamp Life (max)	Weight (g)	Dimensions (HxDia mm)
711260	100W	4000K / 80	13500	N	110°	0.9	50,000	1950	175x262
711261	150W	4000K / 80	20300	N	110°	0.9	50,000	2310	175x301
711263	200W	4000K / 80	27000	N	110°	0.9	50,000	3440	175x350

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +50°C

## INDUSTRIAL | FLOODLIGHT

# VOSS

**MEGAMAN® ESSENTIALS VOSS**  
IS A NEW AND HIGHLY FLEXIBLE  
RANGE OF COST EFFECTIVE AND  
RELIABLE, HIGH LUMEN AND  
ENERGY EFFICIENT LED  
FLOODLIGHTS. IDEAL EVERYDAY  
LIGHTING SOLUTION AT A REALLY  
COMPETITIVE PRICE.

### FEATURES & BENEFITS

- Slim and extra light weight
- Pre-flexed with 500mm fly lead
- Textured diffuser
- Available in 5 different sizes
- Die cast aluminium housing
- IP65 and IK08 rated
- Adjustable fixing bracket  $\pm 180^\circ$
- Wide area floodlight without glare
- Simple installation
- Suitable for outdoor use
- Flexible tilting and positioning
- Corrosion free & UV resistant housing. Tempered glass.



711285 - 10W



711286 - 20W



711288 - 50W



711289 - 100W



711291 - 200W

### Applications

- Commercial
- Domestic outdoor security lighting
- Signage
- Billboards
- Pillar facades
- Gate areas
- Retail



## INDUSTRIAL | FLOODLIGHT

### VOSS INTEGRATED LED FLOODLIGHT

10W-200W | IP65 | 4000K | 900-18000lm | 50,000hrs |



**COST EFFECTIVE** IP65 LED FLOODLIGHTS

**EASY INSTAL WITH** PUSH TO FIT CONNECTORS

**EFFICIENT** HEAT DISSIPATION

**MEGAMAN® ESSENTIALS VOSS** is a new range of cost effective integrated LED floodlights with a slim and efficient heat dissipation profile that offers a wide range of high lumen lighting solution. Equipped with a u-shaped bracket, the luminaire can be rotated 180° adjustment for lighting.




Photometric data:  
Please refer to our  
website for up to  
date photometric  
information.

711291 - 200W



See page 12 for MEGAMAN® **PERFORMA TOTT 2 LED FLOODLIGHT** high performance range.

#### DIMENSIONS



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (L x W x H mm)
711285	10W	4000K / 80	900	N	110°	30,000	270	103x23x104
711286	20W	4000K / 80	1800	N	110°	30,000	340	121x24x119
711288	50W	4000K / 80	4500	N	110°	30,000	740	206x36x195
711289	100W	4000K / 80	9000	N	110°	30,000	1200	274x32x238
711291	200W	4000K / 80	18000	N	110°	30,000	3100	381x40x324

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C



## INDUSTRIAL | FLOODLIGHT

# VOSS with PIR Sensor

**MEGAMAN® ESSENTIALS VOSS IS AN ALL ROUND GREAT VALUE FOR MONEY ROBUST RANGE OF MODERN SLIM LED FLOODLIGHTS WITH PIR SENSOR FOR ADDED SECURITY AND ENERGY SAVING.**

### FEATURES & BENEFITS

- Slim and extra light weight
- Pre-flexed with 500mm fly lead
- Textured diffuser
- Available in 3 different sizes
- Die cast housing
- IP54 and IK08 rated
- Adjustable fixing bracket  $\pm 180^\circ$
- Wide area floodlight without glare
- Simple installation
- Suitable for outdoor use
- Flexible tilting and positioning
- Corrosion free & UV resistant housing. Tempered glass.



PIR Sensor



711292 - 11W



PIR Sensor



711293 - 21W



PIR Sensor



711295 - 51W

### Applications

- Commercial
- Domestic outdoor security lighting
- Signage
- Billboards
- Pillar facades
- Gate areas
- Retail

CALL: 01707 386000  
EMAIL: SALES@MEGAMANUK.COM



## INDUSTRIAL | FLOODLIGHT

### VOSS INTEGRATED LED FLOODLIGHT with PIR Sensor

11W-51W | IP54 | 4000K | 900-45000lm | 50,000hrs |



Photometric data:  
Please refer to our  
website for up to  
date photometric  
information.






**COST EFFECTIVE** IP65 LED FLOODLIGHT

**PIR SENSOR FOR** ADDED SECURITY

**EFFICIENT** HEAT DISSIPATION

**MEGAMAN® ESSENTIALS VOSS** is a new range of cost effective integrated LED floodlights with a slim and efficient heat dissipation profile that offers a wide range of high lumen lighting solution. Equipped with a u-shaped bracket, the luminaire can be rotated 180° adjustment for lighting.

#### DIMENSIONS



See page 12 for MEGAMAN® **PERFORMA TOTT 2 LED FLOODLIGHT** high performance range.

Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (L x W x H mm)
<b>711292</b>	11W	4000K / 80	900	N	110°	30,000	400	104x45x154
<b>711293</b>	21W	4000K / 80	1800	N	110°	30,000	470	121x45x163
<b>711295</b>	51W	4000K / 80	4500	N	110°	30,000	830	206x45x230

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

**BULKHEAD | INDOOR**

# KATIA

MEGAMAN® **ESSENTIALS KATIA** IS A REALLY STYLISH SLIM AND HIGHLY EFFICIENT LED BULKHEAD THAT PROVIDES IS THE IDEAL REPLACEMENT FOR TRADITIONAL CEILING LIGHTING SOLUTIONS.

## FEATURES & BENEFITS

- Round and slim profile
- 4 sizes and wattages to choose from
- Direct alternatives to traditional wall and ceiling lamp
- Easy installation
- IP40 protection
- Operation temperature -20°C to 40°C



Easy Installation



711329 - 12W



711330 - 18W



711331 - 24W



711332 - 36W



## BULKHEAD | INDOOR

# KATIA INTEGRATED LED INDOOR BULKHEAD

12W-36W | IP40 | 4000K | 1200-3600lm | 25,000hrs |



ULTRA SLIM IP40 LED BULKHEAD

EASY TOOLLESS INSTALLATION

FLICKER FREE

### NEW MEGAMAN® ESSENTIALS KATIA

is a new range of cost effective range of stylish and ultra slim integrated LED indoor bulkheads. ESSENTIALS KATIA is designed to provide an even light from either wall or ceiling to illuminate the whole room with comfort.







See page 14 for MEGAMAN® PERFORMA RENZO LED BULKHEAD high performance range.



Photometric data:  
Please refer to our  
website for up to  
date photometric  
information.

### DIMENSIONS



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (Dia x H mm)
711329	12W	4000K / 80	1200	N	120°	25,000	250	220x40
711330	18W	4000K / 80	1800	N	120°	25,000	370	290x42
711331	24W	4000K / 80	2400	N	120°	25,000	530	350x43
711332	36W	4000K / 80	3600	N	120°	25,000	760	450x48

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -20°C to +50°C

**BULKHEAD | OUTDOOR**

# RONDA

**IP65 & IK08 RATED  
ESSENTIALS RONDA  
IS MEGAMAN®'S NEW  
ROBUST AND GREAT  
VALUE FOR MONEY  
ROBUST MODERN  
LED BULKHEAD.  
IDEAL FOR  
DEMANDING  
OUTDOOR  
ENVIRONMENTS.**

## FEATURES & BENEFITS

- Cost effective LED Outdoor Bulk-head solution for mains voltage
- UV resistant opal diffuser
- Robust IK08 vandal resistant
- IP65 waterproof protection
- Up to 92lm/W
- Operation temperature -20°C to 40°C



711411 - 12W



711412 - 18W



711413 - 24W

## Applications

- Car parks
- Warehouses
- Stairwells
- Corridors

CALL: 01707 386000  
EMAIL: SALES@MEGAMANUK.COM

## BULKHEAD | OUTDOOR

# RONDA INTEGRATED LED OUTDOOR BULKHEAD

12W-24W | IP65 | 4000K | 1100-2200lm | 30,000hrs |



**COST EFFECTIVE** IP65 LED BULKHEAD

**CORROSION FREE** PLASTIC HOUSING

**BESA BOX** COMPATIBLE




**Photometric data:**  
Please refer to our website for up to date photometric information.

### NEW MEGAMAN® ESSENTIALS RONDA

is a new round shaped LED bulkhead perfect for outdoor lighting. It is constructed of a corrosion free plastic housing and UV resistant opal diffuser; together with IP65 and IK08 rating, makes RONDA the ideal everyday and reliable economical lighting solution for tough outdoor conditions.

### DIMENSIONS



See page 16 for MEGAMAN® **PERFORMA FONDA LED BULKHEAD** high performance range.

Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (Dia x H mm)
<b>711411</b>	12W	4000K / 80	1100	N	120°	30,000	600	250x100
<b>711412</b>	18W	4000K / 80	1650	N	120°	30,000	800	300x100
<b>711413</b>	24W	4000K / 80	2200	N	120°	30,000	850	300x100

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

**BATTEN | INDOOR**

# GARRON

**MEGAMAN® ESSENTIALS**  
**GARRON** IS A NEW AND  
FLEXIBLE RANGE OF GREAT  
VALUE FOR MONEY INDOOR  
LED BATTENS. OFFERING A  
HARD TO BEAT, GOOD  
QUALITY EVERYDAY  
LIGHTING SOLUTION.

## FEATURES & BENEFITS

- Replacement for conventional indoor batten
- 4 different lengths - 2ft, 4ft, 5ft and 6ft
- Easy installation and toolless wiring
- BESA box compatible
- Traditional batten appearance

**BESA BOX  
COMPATIBLE**

## Applications

- Residential lighting
- Schools
- Corridors
- Warehouses

**2FT  
10/17W**

**4FT  
20/40W**

**5FT  
30/60W**

**6FT  
40/65W**



## BATTEN | INDOOR

# GARRON INTEGRATED LED INDOOR BATTEN

10W-65W | IP20 | 4000K | 1200-7800lm | 30,000hrs |



**Photometric data:**  
Please refer to our  
website for up to  
date photometric  
information.

**COST EFFECTIVE & FLEXIBLE RANGE**



**QUICK & TOOLLESS INSTALLATION**

**BESA BOX COMPATIBLE**

### NEW MEGAMAN® ESSENTIALS

**GARRON** is an economy range of energy saving integrated LED battens. Easy toolless installation and a flexible range of sizes and wattages, makes GARRON a great value for money, everyday good quality lighting replacement for conventional indoor battens.

### DIMENSIONS



Loop through wiring  
adaptor



See page 20 for MEGAMAN® **PERFORMA FARRON LED BATTEN** high performance range.

Order Code		Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxWxH mm)
<b>711338</b>	<b>2ft</b>	10W	4000K / 80	1200	N	110°	30,000	750	620x64x65
<b>711334</b>	<b>2ft</b>	17W	4000K / 80	2040	N	110°	30,000	750	620x64x65
<b>711339</b>	<b>4ft</b>	20W	4000K / 80	2400	N	110°	30,000	1350	1200x64x65
<b>711335</b>	<b>4ft</b>	40W	4000K / 80	4800	N	110°	30,000	1350	1200x64x65
<b>711340</b>	<b>5ft</b>	30W	4000K / 80	3600	N	110°	30,000	1650	1500x64x65
<b>711336</b>	<b>5ft</b>	60W	4000K / 80	7200	N	110°	30,000	1650	1500x64x65
<b>711341</b>	<b>6ft</b>	40W	4000K / 80	4800	N	110°	30,000	1950	1800x64x65
<b>711337</b>	<b>6ft</b>	65W	4000K / 80	7800	N	110°	30,000	?1950	1800x64x65

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C



## BATTEN | WEATHERPROOF IP65



ESSENTIALS  
ROCCA  
TWIN OUTPUT  
IP65 INDOOR  
BATTEN

### FEATURES & BENEFITS

- Replacement for conventional waterproof fluorescent battens
- 3 different length 1200mm, 1500mm and 1800mm
- Easy installation and toolless wiring
- Robust IP65 and IK08 rated
- BESA box compatible
- 40,000 hours rated
- Single and twin output versions

**MEGAMAN® ESSENTIALS ROCCA IS A NEW ROBUST IP65 WEATHERPROOF LED BATTEN THAT COMES IN SINGLE AND TWIN OUTPUT VERSIONS. ROCCA IS THE IDEAL, ENERGY SAVING AND GREAT VALUE FOR MONEY REPLACEMENT FOR TRADITIONAL FLUORESCENT BATTENS.**

### Applications

- Car parks
- Warehouses
- Stairwells
- Corridors

BESA BOX  
COMPATIBLE

CALL: 01707 386000  
EMAIL: SALES@MEGAMANUK.COM



**MEGAMAN®**

• VALUE FOR MONEY • RELIABLE • EVERYDAY • LED FIXTURES •

## BATTEN | WEATHERPROOF IP65

# ROCCA WEATHERPROOF IP65 INTEGRATED LED BATTEN SINGLE & TWIN OUTPUT

20W-35W | IP65 | 4000K | 2500-4200lm | 40,000hrs | Flicker Free



**SINGLE & TWIN & OUTPUT VERSIONS**

**QUICK & TOOLLESS INSTALLATION**

**BESA BOX COMPATIBLE**



**Photometric data:**  
Please refer to our website for up to date photometric information.


### NEW MEGAMAN® ESSENTIALS

**ROCCA** is the ideal LED replacement for traditional fluorescent waterproof battens. Providing a reliable and good quality standard of light; with substantial energy and maintenance savings. Available in both single and twin output versions, new ROCCA is an essential everyday economy lighting solution.



See page 22 for MEGAMAN® **PERFORMA DINO 2 LED BATTEN** high performance range.

### DIMENSIONS



Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxWxH mm)
<b>711345</b> SINGLE OUTPUT	20W	4000K / 80	2500	N	110°	40,000	1200	1270x74x74
<b>711346</b> SINGLE OUTPUT	28W	4000K / 80	3600	N	110°	40,000	1800	1570x74x74
<b>711347</b> SINGLE OUTPUT	34W	4000K / 80	4200	N	110°	40,000	3000	1870x74x74
<b>711342</b> TWIN OUTPUT	40W	4000K / 80	4800	N	110°	40,000	1300	1270x116x74
<b>711343</b> TWIN OUTPUT	56W	4000K / 80	6000	N	110°	40,000	2050	1570x116x74
<b>711344</b> TWIN OUTPUT	70W	4000K / 80	8400	N	110°	40,000	3100	1870x116x74

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +45°C

**DOWNLIGHT | FIRE-RATED**

# TEGO SLIM

BRUSH  
NICKEL  
FINISH



Slim and compact design, ideal for shallow ceiling depth installations

## FEATURES & BENEFITS

- Available as 2800K/430 lumen and 4000K/450 lumen versions
- Toolless wiring block and push-in terminal ensure easy install
- Flexible Loop in/Loop out feature enables for quick connection
- Triac Dimmable as standard
- Available in either White or Brushed Nickel finishes
- IP65 rated. Ideal for high moisture areas e.g. bathrooms
- 3 Year warranty
- Fully fire-rated for 30/60/90 minute ceilings
- Slim and compact design ideal for shallow ceiling recesses
- Competitively priced
- High quality, high performance LED downlight
- Great value 10 Pack

**ESSENTIALS TEGO SLIM IS MEGAMAN®'S FLEXIBLE FIRE-RATED, ECONOMY LED DOWNLIGHT THAT FEATURES FLEXIBLE LOOP IN/LOOP OUT TERMINALS AND TOOLLESS WIRING FOR QUICK INSTALLATION.**



Flexible cord between luminaire and terminal block that facilitates easy installation



## DOWNLIGHT | FIRE-RATED

# TEGO SLIM INTEGRATED FIRE-RATED LED DOWNLIGHT

5.5W | IP65 | 2800-4000K | 430-450lm | 25,000hrs |



**COMPACT & SLIM IP65 LED DOWNLIGHT**

**FIRE-RATED 30/60/90 MINUTE**

**TRIAC DIMMING AS STANDRAD**





**Photometric data:**  
Please refer to our website for up to date photometric information.

**MEGAMAN®'s new ESSENTIALS TEGO SLIM** is a compact and slim design LED downlight that's ideal for shallow ceiling recesses. Flexible Loop in/loop out feature and toolless wiring enables quick connection and installation.

TEGO Slim is IP65 rated, making it ideal for use in high moisture areas such as bathrooms & kitchens. Available with either White or Brush Nickel bezel finishes.

### DIMENSIONS



Loop through wiring adaptor



See page 28 for MEGAMAN® **PERFORMA TEGO 2 FULLY FIRE-RATED LED DOWNLIGHT** high performance range.

Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Beam Angle	Hrs Lamp Life (max)	Hole Cut-Out (mm)	Dimensions (Dia x H mm)
<b>711126</b> 10 PACK MATT WHITE	5.5W	2800K / 80	430	Y	90°	25,000	70	83x51
<b>711128</b> 10 PACK BRUSHED NICKEL	5.5W	2800K / 80	430	Y	90°	25,000	70	83x51
<b>711140</b> 10 PACK MATT WHITE	5.5W	4000K / 80	450	Y	90°	25,000	70	83x51
<b>711142</b> 10 PACK BRUSHED NICKEL	5.5W	4000K / 80	450	Y	90°	25,000	70	83x51

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +45°C

**DOWNLIGHT | INDOOR**

# MILENALITE

15W  
3000K  
4000K  
6500K



24W  
3000K  
4000K  
6500K



## FEATURES & BENEFITS

- Recessed integrated LED downlight
- Available in 3000K, 4000K and 6500K colour temperatures
- Built-in driver
- IP20 and IK03
- 25,000 hours rated life (L70 B50 at Ta 25°C)
- Low in height and suitable for limited ceiling depths
- No external driver required which facilitates easy installation and maintenance
- Milenalite is ideal for retrofit in existing conventional installations and their ceiling cut-outs
- Wide and uniform light distribution

**ESSENTIALS MILENALITE IS  
MEGAMAN®'S FLEXIBLE  
NEW COMPACT AND SLIM  
ECONOMY RECESSED DOWNLIGHT.  
IDEAL RETROFIT REPLACEMENT  
FOR CONVENTIONAL DOWNLIGHTS  
& THEIR EXISTING CUT-OUTS.**

## Applications:

- General purpose applications
- Retail
- Hotels
- Offices
- Restaurants

CALL: 01707 386000  
EMAIL: SALES@MEGAMANUK.COM

## DOWNLIGHT | INDOOR

# MILENALITE INTEGRATED LED DOWNLIGHT

15W-24W | IP20 | 3000-6500K | 1300-1950lm | 30,000hrs |



**NO EXTERNAL DRIVER NEEDED**

**IDEAL RETROFIT FOR CONVENTIONAL DOWNLIGHTS**



**SLIM DESIGN FOR LIMITED CEILING DEPTHS**



**Photometric data:**  
Please refer to our website for up to date photometric information.

**MEGAMAN® ESSENTIALS MILENALITE** is a cost effective replacement for traditional PL commercial downlights with high luminous efficacy and energy saving benefits. MEGAMAN® MILENALITE is a compact and slim integrated LED downlight perfect for use in limited ceiling depths and in existing ceiling cut-outs of conventional recessed downlight installations .

### DIMENSIONS



See page 31 for MEGAMAN® PERFORMA MILENA DOWNLIGHT high performance range.

Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	IP Rating (IP)	Colour/ Finish	Dimmable	Hrs Lamp Life (max)	Dimensions (HxDia mm)	Hole Cut-Out (mm)	Beam Angle
710871	15W	3000K / 80	1300	IP20	White	N	25,000	30x175	150	120°
710872	15W	4000K / 80	1300	IP20	White	N	25,000	30x175	150	120°
710873	15W	6500K / 80	1300	IP20	White	N	25,000	30x175	150	120°
710874	24W	3000K / 80	1950	IP20	White	N	25,000	30x225	200	120°
710875	24W	4000K / 80	1950	IP20	White	N	25,000	30x225	200	120°
710876	24W	6500K / 80	1950	IP20	White	N	25,000	30x225	200	120°

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C



**COMMERCIAL | LED PANEL**

# KANA

## FEATURES & BENEFITS

- Compact recessed integrated LED downlight
- Flicker Free
- IP40
- 30,000 hours rated life (L70 B50 at Ta 25°C)
- Replacement for traditional CFL downlights
- No external driver required which facilitates easy installation and maintenance
- Delivers uniform light distribution
- Range of sizes allowing retrofit for many conventional downlights in existing ceiling cut-outs
- Slim design suitable for limited ceiling depths



**NEW ESSENTIALS KANA IS A RELIABLE AND COST EFFECTIVE COMPACT ECONOMY RECESSED DOWNLIGHT. IDEAL RETROFIT REPLACEMENT FOR CONVENTIONAL DOWNLIGHTS AND THEIR EXISTING CUT-OUTS. SAVING TIME & MONEY.**

### Applications:

- Retail
- Hotels
- Offices
- Restaurants
- Bathroom



## COMMERCIAL | LED PANEL

### KANA INTEGRATED LED DOWNLIGHT

7W-25W | IP40 | 3000-4000K | 560-2000lm | 30,000hrs | Flicker Free



**NO EXTERNAL DRIVER NEEDED**

**IDEAL RETROFIT** FOR CONVENTIONAL DOWNLIGHTS

**SLIM DESIGN** FOR LIMITED CEILING DEPTHS

**MEGAMAN® ESSENTIALS KANA** is a cost effective replacement for traditional PL commercial downlights with high luminous efficacy and energy saving benefits. New KANA is a compact and slim integrated LED downlight perfect for use in limited ceiling depths and inexisting ceiling cut-outs of conventional recessed downlight installations .




**BRINGING YOU MORE CHOICE!**

See page **30** for MEGAMAN® **PERFORMA MILENA LED DOWNLIGHT** high performance range.



**Photometric data:**  
Please refer to our website for up to date photometric information.

#### DIMENSIONS



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	IP Rating (IP)	Colour/ Finish	Dimmable	Hrs Lamp Life (max)	Dimensions (HxDia mm)	Hole Cut-Out (mm)	Beam Angle
711417	7W	4000K / 80	560	IP40	White	N	30,000	30x115	78	120°
711418	10W	4000K / 80	800	IP40	White	N	30,000	30x145	106	120°
711419	13W	4000K / 80	1040	IP40	White	N	30,000	30x175	125	120°
711420	19W	4000K / 80	1520	IP40	White	N	30,000	32x195	138	120°
711421	25W	4000K / 80	2000	IP40	White	N	30,000	35x225	165	120°

Output and lamp life stated are maximum 'up to' figures achieved. Operating temperature -30°C to +40°C

# TEMPUS® EMERGENCY LIGHTING

ALL  
ROUND  
BEST VALUE  
&  
CHOICE

MEGAMAN® ESSENTIALS  
TEMPUS® new range of  
everyday great value for  
money maintained and  
non-maintained emergency  
lighting solutions.

# TEMPUS® EMERGENCY LIGHTING |



SLIM IP65 BULKHEAD P84



SUSPENDED EXIT SIGN P87



OPEN AREA DOWNLIGHT P90



EXIT METAL LIGHT BOX P85



OPEN AREA RECESSED DOWNLIGHT P88



CORRIDOR DOWNLIGHT P91



EXIT PLASTIC SIGN P86



CORRIDOR RECESSED DOWNLIGHT P89



EMERGENCY TWIN SPOT P92

### TEMPUS® EMERGENCY LIGHTING |



## SLIM BULKHEAD EMERGENCY 3 HOUR MAINTAINED / NON-MAINTAINED

4W | IP65 | 6500K | 140lm | 3 hrs |



### IP65 EMERGENCY BULKHEAD

### FAST & EASY SURFACE MOUNTED INSTAL


### 3 HOUR EMERGENCY POWER TIME



#### FEATURES & BENEFITS

- 3 hour power time duration
- Included advanced high specification Ni-MH battery
- IP65 dust and weatherproof
- Corrosion resistant, durable polycarbonate housing
- Maintained/Non-maintained operation mode
- Green colour status LED indicator
- All direction exit sign stickers included
- Fast & easy surface mounted installation
- Multi-purpose application

#### DIMENSIONS



All direction exit sign stickers included



See page 46 for MEGAMAN® **PERFORMA TEMPUS®** SELF-TEST EMERGENCY SLIM BULKHEAD performance option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
<b>710474</b>	4W	6500K	140	3.6V 1000mAh Ni-MH	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	610	352x110x67

## TEMPUS® EMERGENCY LIGHTING |



# EXIT METAL LIGHT BOX EMERGENCY 3 HOUR MAINTAINED / NON-MAINTAINED

5W | IP20 | 6500K | 35lm | 3hrs |



**MULTI-PURPOSE** APPLICATION

**ANTI-CORROSION** STEEL HOUSING


**3 HOUR EMERGENCY** POWER TIME



### FEATURES & BENEFITS

- 3 hour power time duration
- Included advanced high specification Ni-Cd battery
- Durable steel housing with anti-corrosion powder coating
- Maintained / Non-maintained operation mode
- Integral green colour status LED indicator
- Supplied with arrow down legend - other options available
- Light weight for easy wall installation
- Easy to swap/replace directional legend
- Multi-purpose application

### DIMENSIONS



### ACCESSORIES

- 710478** Arrow Left Legend  
**710479** Arrow Right Legend  
**710491** Arrow Up Legend



See page 47 for MEGAMAN® **PERFORMA TEMPUS®**  
**SELF-TEST METAL EXIT LIGHT BOX** high performance option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
<b>710476</b>	5W	6500K	35	3.6V 1800mAh Ni-Cd	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	1330	390x190x62



## TEMPUS® EMERGENCY LIGHTING |



# SUSPENDED EMERGENCY EXIT SIGN CEILING OR CORD MOUNTED 3 HOUR NON-MAINTAINED

3.5W | IP20 | 6500K | 35lm | 3 hrs |



**ULTRA SLIM** EMERGENCY EXIT SIGN

**FLEXIBLE CEILING** OR CORD MOUNTED


**3 HOUR EMERGENCY** POWER TIME



### FEATURES & BENEFITS

- Ceiling and cord suspended emergency exit sign
- 3 hour power time duration
- 24 hour charge time
- Included advanced high specification Ni-MH battery
- 850°C glow-wiring test
- Non-maintained operation mode
- Green colour status LED indicator
- Polycarbonate construction
- Light in weight for easy install
- Flexible ceiling & cord suspended mounted in one fitting
- Max. 350mm length suspension cord
- Easy mounting 2-side pictograms options available

### DIMENSIONS



### ACCESSORIES

- 710489** Arrow Left/Right Legend  
**710492** Arrow Up Legend



See page 49 for MEGAMAN® SELF-TEST PERFORMA TEMPUS® RECESSED SLIM EMERGENCY EXIT SIGN option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
<b>710487</b>	3.5W	6500K	35	3.6V 1000mAh Ni-Mh	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	1330	316x24x235 -576

## TEMPUS® EMERGENCY LIGHTING |



# PLASTIC EMERGENCY EXIT WALL MOUNTED 3 HOUR NON-MAINTAINED

3.5W | IP20 | 6500K | 35lm | 3 hrs |



**ULTRA SLIM** EMERGENCY EXIT SIGN

**NEAT POLYCARBONATE** PICTURE FRAME STYLE


**3 HOUR EMERGENCY** POWER TIME



### FEATURES & BENEFITS

- Wall mounted emergency exit sign
- 3 hour power time duration
- 24 hour charge time
- Included advanced high specification Ni-MH battery
- 850°C glow-wiring test
- Non-maintained operation mode
- Green colour status LED indicator
- Polycarbonate construction
- Light in weight for easy install
- Easy mounting 1-side pictogram options available

### DIMENSIONS



### ACCESSORIES

**710489** Arrow Left/Right Legend  
**710492** Arrow Up Legend



See page 48 for MEGAMAN® **PERFORMA TEMPUS®**  
**EMERGENCY EMERGENCY EXIT** high performance option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
<b>710488</b>	3.5W	6500K	35	3.6V 1000mAh Ni-Mh	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	1330	316x24x196

## TEMPUS® EMERGENCY LIGHTING |



# OPEN AREA DOWNLIGHT EMERGENCY RECESSED 3 HOUR NON-MAINTAINED

1W | IP20 | 6000K | 120lm | 3 hrs |



**IP20 SELF-TEST ULTRA-LOW PROFILE DOWNLIGHT**

**FAST & EASY RECESSED INSTALLATION**


**3 HOUR EMERGENCY POWER TIME**



### FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- IP20 polycarbonate housing
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch testing button
- 850°C glow-wiring test
- 50,000 hours rated life Green colour status LED indicator
- SELV Constant current output
- Comply with EN 60598-2-22, UN 38.3 & IEC 62133

### DIMENSIONS



ø36mm Hole Cut-out



See page 54 for MEGAMAN® PERFORMA TEMPUS®  
SELF-TEST RECESSED OPEN AREA DOWNLIGHT option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (WxDia mm)
<b>710480</b>	1W	6000K	120	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	140°	23x40

## TEMPUS® EMERGENCY LIGHTING |



# CORRIDOR DOWNLIGHT EMERGENCY RECESSED 3 HOUR NON-MAINTAINED

1W | IP20 | 6000K | 120lm | 3 hrs |



**IP20 SELF-TEST ULTRA-LOW PROFILE DOWNLIGHT**

**FAST & EASY RECESSED INSTALLATION**


**3 HOUR EMERGENCY POWER TIME**



### FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- IP20 polycarbonate housing
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch testing button
- 850°C glow-wiring test
- 50,000 hours rated life
- Green colour status LED indicator
- SELV Constant current output
- Comply with EN 60598-2-22, UN 38.3 & IEC 62133

### DIMENSIONS



ø36mm Hole Cut-out



See page 55 for MEGAMAN® PERFORMA TEMPUS®  
SELF-TEST EMERGENCY CORRIDOR DOWNLIGHT option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (WxDia mm)
<b>710481</b>	1W	6000K	120	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	140°	23x40

**TEMPUS® EMERGENCY LIGHTING |**



# OPEN AREA DOWNLIGHT EMERGENCY SURFACE MOUNTED 3 HOUR NON-MAINTAINED

1W | IP54 | 6000K | 130lm | 3 hrs |



**IP54 SELF-TEST COMPACT DOWNLIGHT**

**FAST & EASY SURFACE MOUNTED INSTAL**


**3 HOUR EMERGENCY POWER TIME**



## FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- IP54 polycarbonate housing
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch testing button
- 850°C glow-wiring test
- 50,000 hours rated life
- Green colour status LED indicator
- Multi-purpose application
- Comply with EN 60598-2-22,

## DIMENSIONS



See page 52 for MEGAMAN® **PERFORMA TEMPUS®**  
**SELF-TEST EMERGENCY OPEN AREA DOWNLIGHT** option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (LxWxH mm)
<b>710482</b>	1W	6000K	135	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	140°	130x130x35

## TEMPUS® EMERGENCY LIGHTING |



# CORRIDOR DOWNLIGHT EMERGENCY SURFACE MOUNTED 3 HOUR NON-MAINTAINED

1W | IP54 | 6000K | 200lm | 3 hrs |



**IP54 SELF-TEST COMPACT DOWNLIGHT**

**FAST & EASY SURFACE MOUNTED INSTAL**


**3 HOUR EMERGENCY POWER TIME**



### FEATURES & BENEFITS

- 3 hour power time duration
- 16 hour charge time
- Included advanced high specification LiFePO4 battery
- IP54 polycarbonate housing
- Over-charge and over-discharge protection
- Over-temperature and short circuit protection
- Touch testing button
- 850°C glow-wiring test
- 50,000 hours rated life
- Green colour status LED indicator
- Multi-purpose application
- Comply with EN 60598-2-22,

### DIMENSIONS



See page 53 for MEGAMAN® PERFORMA TEMPUS®  
SELF-TEST EMERGENCY CORRIDOR DOWNLIGHT option.

Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Beam Angle	Dimensions (LxWxH mm)
<b>710483</b>	1W	6000K	135	3.2V 1500mAh LiFePO4	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	140°	130x130x35



**TEMPUS® EMERGENCY LIGHTING |**



# TWIN SPOT IP65 EMERGENCY 3 HOUR NON-MAINTAINED

2.3W | IP65 | 6500K | 400lm | 3 hrs |



**DURABLE IP65 EMERGENCY TWIN SPOT**

**CORROSION RESISTANT POLYCARBONATE DIFFUSER**


**3 HOUR EMERGENCY POWER TIME**



## FEATURES & BENEFITS

- 3 hour power time duration
- 24 hour charge time
- Included advanced high specification Ni-cd battery
- IP65 rated
- Polycarbonate diffuser, corrosion resistant
- Rotate and tilt lighting direction
- 850°C glow-wiring test
- Non-maintained operation mode
- Green colour status LED indicator
- Light in weight for easy install

## DIMENSIONS



Order Code	Watts	Colour Temp (K)	Lumens (lm)	Battery	Battery Duration	Working Temp.	Rated Supply	Weight (g)	Dimensions (LxWxH mm)
<b>710485</b>	2.3W	6500K	400	12V 1500mAh Ni-cd	3 hours	0°C - +40°C	220-240VAC / 50-60Hz	1330	300x82x294

## TEMPUS® EMERGENCY LIGHTING |



MEGAMAN® PERFORMA TEMPUS®. A comprehensive range of high quality and performance, maintained and non-maintained **self-test** emergency lighting solutions.

Go to page 44 to see the full range.



**MEGAMAN®**  
**Performa**  
FIXTURE RANGE  
HIGH PERFORMANCE & QUALITY FROM MEGAMAN®

**TEMPUS®**  
**EMERGENCY**  
**SELF-TEST**  
**LIGHTING**

# MEGAMAN® LED LAMPS

MEGAMAN® comprehensive range of Economy and Professional LED lamps that provide both great value for money and high performance. Up to 3 years warranty and 50,000 hours.

## ECONOMY & PROFESSIONAL SERIES |



GU10 LED P98 - P107



GOLF BALL LED P128 - P131



FILAMENT GOLF BALL LED P144 - P146



GX53 LED P153 - P154



GU4 LED P108



GLOBE P152



FILAMENT ST64 LED P147 - P149



G9 LED P155 - P156



AR111 LED P110 - P112



FILAMENT CLASSIC LED P134 - P140



T8 TUBE LED P150



G4 LED P157



OPAL CLASSIC LED P114 - P123



FILAMENT CANDLE LED P141 - P145



PAR30s LED P152



CLUSTERLITE® LED P158 - P160



OPAL CANDLE P124 - P127



## MEGAMAN® DUAL BEAM TECHNOLOGY |

### BRINGING YOU THE CHOICE OF TWO BEAM ANGLES IN ONE LUMINAIRE

**MEGAMAN® pioneered an innovative approach for switching the size of the light spot with a simple push action on luminaires featured with Dual Beam Technology (patent pending). With this technology one can shape the light spot of the luminaire from a narrow beam to a wider beam angle.**

The term "Dual Beam" refers to the dual function of a luminaire. It can be set to project a narrow beam or a wider beam. Luminaires with "Dual Beam" function provide users unparalleled flexibility and convenience when adjusting the contrast between ambient and accent lighting on-site, eliminating the hustle and bustle of changing luminaire with a different beam angle. In some cases, fixtures with specific beam angle are not readily available and subsequent arrangement will cause inevitable delay in completing projects. Choosing luminaires equipped with MEGAMAN®'s Dual Beam Technology will put you at ease when doing projects.

#### How It Works

The mechanism that makes Dual Beam illumination possible is cleverly engineered into the DBT-enabled luminaire. To shape the beam angle of such luminaire, simply apply a push action on the front lens. This unique mechanism enables users to switch beam angles instantly from a narrow beam to a wider beam and vice versa.



#### 5.2W, 5.3W Dual Beam Technology GU10

**144000** - 5.2W, 2800K, Dimmable, 24°/35°  
**144002** - 5.2W, 4000K, Dimmable, 24°/35°



[GO TO PAGE 108](#)

**140522** - 5.2W, 2800K, Dimmable, 40°/60°  
**140524** - 5.2W, 4000K, Dimmable, 40°/60°  
**140526** - 5.2W, 6500K, Dimmable, 40°/60°



[GO TO PAGE 107](#)

**140516** - 5.3W, 2800K, Dimmable, 24°/35°  
**140518** - 5.3W, 4000K, Dimmable, 24°/35°  
**140520** - 5.3W, 6500K, Dimmable, 24°/35°



[GO TO PAGE 109](#)




#### 11W AR111 Dual Beam Technology GU10

**142624** - 11W, 2800K, U-DIM™, 24°/45°  
**142626** - 11W, 4000K, U-DIM™, 24°/45°



[GO TO PAGE 114](#)



#### 11W, 13W AR111 Dual Beam Technology G53

**142616** - 11W, 2800K, Dimmable, 24°/45°  
**142618** - 11W, 4000K, Dimmable, 24°/45°



[GO TO PAGE 112](#)

**142620** - 13W, 2800K, Dimmable, 24°/45°  
**142622** - 13W, 4000K, Dimmable, 24°/45°



[GO TO PAGE 113](#)

# DBT

## MEGAMAN® DUAL BEAM TECHNOLOGY |



TAKE A LOOK AT MARCO MIDI  
Optional Integrated Dual Beam LED  
Track Light (24W)  
GO TO PAGES 39



MEGAMAN® Dual Beam Technology (DBT) offers a flexible choice of beam angles and is available in MARCO MIDI integrated LED tracklight. This innovative dual beam design is ideal for changing one visual effect and facilitating the inventory management.



Wide flood



Narrow flood



MEGAMAN® DBT Technology offers the flexibility of changing the product's beam angle on site with a simple fingertip push action.

- Compact Optical Design
- Dynamic full control of two beam angles in one luminaire
- Also available in PAR16 and AR111 reflectors



GU10 LED | ECONOMY SERIES with 2 Year Warranty

4.2W GU10  
PAR16 LED




- WATTAGE > 4.2W
- LUMENS > 410
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K/4000K/6500K
- LAMP BASE > GU10

MEGAMAN® ECONOMY SERIES PAR16 GU10, perfect for retrofit applications such as showrooms, reception areas, meeting rooms, offices, restaurants, lounges and kitchens.

Applications:  
General domestic and commercial

140510 / 140512 / 140514



LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
140510	4.2W	2800K / 80	410	N	GU10	36°	15,000	28	55x50
140512	4.2W	4000K / 80	410	N	GU10	36°	15,000	28	55x50
140514	4.2W	6500K / 80	410	N	GU10	36°	15,000	28	55x50

GU10 LED | ECONOMY SERIES with 2 Year Warranty

5W GU10 DIMMING  
PAR16 LED



WATTAGE > 5W

LUMENS > 410

HOURS LAMP LIFE > 25,000

DIMMABLE > YES


COLOUR TEMP. > 2800K/4000K

LAMP BASE > GU10

**MEGAMAN® ECONOMY SERIES** PAR16 GU10, perfect for retrofit applications such as showrooms, reception areas, meeting rooms, offices, restaurants, lounges and kitchens.

Applications:  
General domestic and commercial

140500 / 140502



LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
140500	5W	2800K / 80	410	Y	GU10	36°	25,000	33	55x50
140502	5W	4000K / 80	410	Y	GU10	36°	25,000	33	55x50

GU10 LED | ECONOMY SERIES with 2 Year Warranty

4.2W/5W GU10 | 5 PACK  
PAR16 LED

01

PAR16 LED GU10 GROUP

PER BOX

1/20

2YR

WARRANTY





- WATTAGE > 4.2W/5W
- LUMENS > 360
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > GU10

MEGAMAN® ECONOMY SERIES 5 PACK of great value for money PAR16 GU10, perfect for retrofit applications such as showrooms, reception areas, meeting rooms, offices, restaurants, lounges and kitchens.

Applications:  
General domestic and commercial

710390 / 710391



Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
710390	5W	2800K / 80	360	N	GU10	36°	15,000	28	53x50
710391E	4.2W	4000K / 80	360	N	GU10	36°	15,000	28	53x50

GU10 LED | ECONOMY SERIES with 2 Year Warranty

5W GU10 DIMMING  
74mm LED




- WATTAGE > 5W
- LUMENS > 330
- HOURS LAMP LIFE > 25,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > GU10

**MEGAMAN® ECONOMY SERIES** 74mm long neck GU10 suitable for older fire rated fittings, replacing the Megaman 11W CFL GU10 Dimming.

Applications:  
General domestic and commercial

141510 / 141580



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
141510	5W	2800K / 80	330	Y	GU10	90°	25,000	56	74x50
141580	5W	4000K / 80	330	Y	GU10	90°	25,000	58	74x50

## GU10 LED | ECONOMY SERIES with 2 Year Warranty



GU10 LED | ECONOMY SERIES with 2 Year Warranty

5.5W GU10 COMPACT DIMMING  
GLASS FINISH PAR16 LED




- WATTAGE > 5.5W
- LUMENS > 390
- HOURS LAMP LIFE > 15,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K/4000K/6500K
- LAMP BASE > GU10

MEGAMAN® ECONOMY SERIES PAR16 GU10 with glass finish, is an impressive high power 4.5W quality LED lamp. Ideal for low usage commercial outlets and domestic applications.

Applications:  
General domestic and commercial

142220 / 142222 / 142224



LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142220	5.5W	2800K / 80	390	Y	GU10	36°	15,000	50	55x50
142222	5.5W	4000K / 80	390	Y	GU10	36°	15,000	50	55x50
142224	5.5W	6500K / 80	390	Y	GU10	36°	15,000	50	55x50



GU10 LED | PROFESSIONAL SERIES with 3 Year Warranty

5.5W GU10 DIMMING  
PAR16 LED




- WATTAGE > 5.5W
- LUMENS > 500
- HOURS LAMP LIFE > 25,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K/4000K/6500K
- LAMP BASE > GU10

**MEGAMAN® ECONOMY SERIES** PAR16 GU10 is an impressive high power 5.5W and dimmable high quality LED lamp. Ideal for retrofit applications such as showrooms, reception areas, meeting rooms, offices, restaurants, lounges and kitchens.

Applications:  
General domestic and commercial

140504/140506 / 140508



LAMP BASE




Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
140504	5.5W	2800K / 80	500	Y	GU10	36°	25,000	33	55x50
140506	5.5W	4000K / 80	500	Y	GU10	36°	25,000	33	55x50
140508	5.5W	6500K / 80	500	Y	GU10	36°	25,000	33	55x50

**GU10 LED | PROFESSIONAL SERIES** with 3 Year Warranty

## 5.2W GU10 DIMMING DUAL BEAM 40°/60° PAR16 LED



140522 / 140524 / 140526



Go to page 39 to see how this innovative new lamp technology combines together with our **MARCO** fixture to create an integrated **LED Track Light** that offers superb beam quality and control that is ideal for numerous applications.

**WATTAGE > 5.2W**

**LUMENS > 430**

**HOURS LAMP LIFE > 25,000**

**DIMMABLE > YES**

**COLOUR TEMP. > 2800K/4000K/6500K**

**LAMP BASE > GU10**

### MEGAMAN® PROFESSIONAL SERIES

5.2W Dimmable PAR16 incorporates the groundbreaking LED beam shaping technology - **Dual Beam Technology (DBT)**, which enables for the flexible and precise changing of the beam angle on site from 40 to 60 degrees. Ideal for creating either ambient or accent lighting.

### Applications:

General domestic, retail, hospitality, exhibition and museums

### LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
140522	5.2W	2800K / 80	430	Y	GU10	40° / 60°	25,000	42	56x50
140524	5.2W	4000K / 80	430	Y	GU10	40° / 60°	25,000	42	56x50
140526	5.2W	6500K / 80	430	Y	GU10	40° / 60°	25,000	42	56x50

GU10 LED | PROFESSIONAL SERIES with 3 Year Warranty

5.2W GU10 DIMMING DUAL BEAM 24°/ 35° PAR16 LED




- WATTAGE > 5.2W
- LUMENS > 430
- HOURS LAMP LIFE > 25,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > GU10

**MEGAMAN® PROFESSIONAL SERIES**  
5.2W Dimmable PAR16 incorporates the groundbreaking LED beam shaping technology - **Dual Beam Technology (DBT)**, which enables for the flexible and precise changing of the beam angle on site from 24 to 35 degrees. Ideal for creating either ambient or accent lighting.

**Applications:**  
General domestic, retail, hospitality, exhibition and museums

144000 / 144002 /



Go to page 39 to see how this innovative new lamp technology combines together with our **MARCO fixture** to create an integrated **LED Track Light** that offers superb beam quality and control that is ideal for numerous applications.

LAMP BASE



Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
144000	5.2W	2800K / 80	430	Y	GU10	24° / 35°	25,000	42	56x50
144002	5.2W	4000K / 80	430	Y	GU10	24° / 35°	25,000	42	56x50

GU10 LED | PROFESSIONAL SERIES with 3 Year Warranty


5.3W GU10 DIMMING DUAL BEAM 24°/ 35°  
PAR16 LED





140516 / 140518 / 140520





Go to page 39 to see how this innovative new lamp technology combines together with our MARCO fixture to create an integrated LED Track Light that offers superb beam quality and control that is ideal for numerous applications.

WATTAGE > 5.3W

LUMENS > 550

HOURS LAMP LIFE > 25,000

DIMMABLE > YES

COLOUR TEMP. > 2800K/4000K/6500K

LAMP BASE > GU10

**MEGAMAN® PROFESSIONAL SERIES**  
5.2W Dimmable PAR16 incorporates the groundbreaking LED beam shaping technology - **Dual Beam Technology (DBT)**, which enables for the flexible and precise changing of the beam angle on site from 24 to 35 degrees. Ideal for creating either ambient or accent lighting.

Applications:  
General domestic, retail, hospitality, exhibition and museums

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
140516	5.3W	2800K / 80	550	Y	GU10	24° / 35°	25,000	42	56x50
140518	5.3W	4000K / 80	550	Y	GU10	24° / 35°	25,000	42	56x50
140520	5.3W	6500K / 80	550	Y	GU10	24° / 35°	25,000	42	56x50

MR11 LED | PROFESSIONAL SERIES with 3 Year Warranty

3W GU4  
MR11 LED




- WATTAGE > 3W
- LUMENS > 230
- HOURS LAMP LIFE > 25,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > GU4

**MEGAMAN® PROFESSIONAL SERIES**  
LED GU4 MR11 reflector is the eco-conscious and economical alternative to traditional halogen MR11's with the same compact profile.

Applications:  
General domestic and commercial

142630/142632



LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Voltage	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142630	3W	2800K / 80	230	AC12V	N	GU4	36°	25,000	19	38x35
142632	3W	4000K / 80	230	AC12V	N	GU4	36°	25,000	19	38x35

## MR11 LED | PROFESSIONAL SERIES with 3 Year Warranty





AR111 LED | PROFESSIONAL SERIES with 3 Year Warranty

11W AR111 DIMMING DUAL BEAM 24°/ 45°  
G53 12V LED




- WATTAGE > 11W
- LUMENS > 750
- HOURS LAMP LIFE > 40,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K/4000k
- LAMP BASE > G53

MEGAMAN® PROFESSIONAL SERIES

11W AR111 incorporates the ground-breaking Dual Beam Technology (DBT), which enables for the flexible and precise changing of the beam angle on site from 24 to 45 degrees and is available in both 2800K and 4000K colour temperatures. Ideal for creating either ambient or accent lighting for a variety of applications.

Applications:  
General domestic and commercial

142616 / 142618



RECOMMENDED TRANSFORMER:  
Varilight YT50LZ (One transformer per lamp)



Go to page 39 to see how this innovative new lamp technology combines together with our MARCO fixture to create an integrated LED Track Light that offers superb beam quality and control that is ideal for numerous applications.

LAMP BASE




Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Voltage	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142616	11W	2800K / 80	750	AC12V	Y	G53	24°/45°	40,000	225	58x111
142618	11W	4000K / 80	750	AC12V	Y	G53	24°/45°	40,000	225	58x111

AR111 LED | PROFESSIONAL SERIES with 3 Year Warranty

13W AR111 DIMMING DUAL BEAM 24°/ 45°  
G53 12V LED



142620 / 142622



**RECOMMENDED TRANSFORMER:**  
Varilight YTS0LZ (One transformer per lamp)

**DBT**

**24° / 45°**

Go to page 39 to see how this innovative new lamp technology combines together with our MARCO fixture to create an integrated LED Track Light that offers superb beam quality and control that is ideal for numerous applications.

- WATTAGE > 13W
- LUMENS > 900
- HOURS LAMP LIFE > 40,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > G53

**MEGAMAN® PROFESSIONAL SERIES**  
13W AR111 incorporates the ground-breaking Dual Beam Technology (DBT), which enables for the flexible and precise changing of the beam angle on site from 24 to 45 degrees and is available in both 2800K and 4000K colour temperatures. Ideal for creating either ambient or accent lighting for a variety of applications.

Applications:  
General domestic and commercial



Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Voltage	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142620	13W	2800K / 80	900	AC12V	Y	G53	24°/45°	40,000	230	58x111
142622	13W	4000K / 80	900	AC12V	Y	G53	24°/45°	40,000	230	58x111

AR111 LED | PROFESSIONAL SERIES with 3 Year Warranty

11W AR111 DIMMING DUAL BEAM 24°/ 45° GU10 LED







- WATTAGE > 11W
- LUMENS > 900
- HOURS LAMP LIFE > 40,000
- DIMMABLE > YES
- COLOUR TEMP. > 2700K/4000K
- LAMP BASE > GU10

MEGAMAN® PROFESSIONAL SERIES

11W AR111 incorporates the ground-breaking Dual Beam Technology (DBT), which enables for the flexible and precise changing of the beam angle on site from 24 to 45 degrees and is available in both 2800K and 4000K colour temperatures. Ideal for creating either ambient or accent lighting for a variety of applications.

Applications:  
General domestic and commercial

142624 / 142626



Go to page 39 to see how this innovative new lamp technology combines together with our MARCO fixture to create an integrated LED Track Light that offers superb beam quality and control that is ideal for numerous applications.

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Beam Angle	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142624	11W	2700K / 80	900	Y	GU10	24°/45°	40,000	236	82x111
142626	11W	4000K / 80	900	Y	GU10	24°/45°	40,000	236	82x111

## AR111 LED | PROFESSIONAL SERIES with 3 Year Warranty



MEGAMAN® LED LAMPS | AR111 LED

OPAL CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

4.8W OPAL CLASSIC LED



330°



13 MODELS PER BOX



PER BOX 1/60

2YR WARRANTY



WATTAGE > 4.8W

LUMENS > 470

HOURS LAMP LIFE > 15,000

DIMMABLE > NO

COLOUR TEMP. > 2800K

LAMP BASE > E27/B22

**MEGAMAN® ECONOMY OPAL CLASSIC** a high lumen classic shaped LED lamp with intelligent heat sink design. The lamp has even light distribution with 330° illumination and excellent colour rendering of up to Ra80. Eco-conscious replacement for halogens and incandescent lamps.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
143360E	4.8W	2700K / 80	470	N	E27	97	15,000	27	74x50
143362E	4.8W	2700K / 80	470	N	B22	97	15,000	29	74x50

MEGAMAN® LED LAMPS | OPAL CLASSIC LED

## OPAL CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

### 8.6W/9.5W OPAL CLASSIC LED



**WATTAGE > 8.6W/9.5W**

**LUMENS > 810**

**HOURS LAMP LIFE > 15,000**

**DIMMABLE > NO**

**COLOUR TEMP. > 2700K/4000K/6500K**

**LAMP BASE > E27/B22**

**MEGAMAN® 9.5W ECONOMY OPAL CLASSIC** is a high lumen classic shaped LED lamp with intelligent heat sink design. The lamp has even light distribution with 330° illumination and high colour rendering of Ra80 and or above.

Applications:  
General domestic and commercial

#### LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
143316E	8.6W	2700K / 80	810	N	E27	94	15,000	30	109x60
143318E	8.6W	2700K / 80	810	N	B22	94	15,000	32	107x60
143372E	8.6W	4000K / 80	810	N	E27	94	15,000	30	109x60
143370	9.5W	4000K / 80	810	N	B22	85	15,000	32	107x60
143374	9.5W	6500K / 80	810	N	E27	85	15,000	30	109x60
143376E	8.6W	6500K / 80	810	N	B22	94	15,000	32	107x60



**OPAL CLASSIC LED | ECONOMY SERIES** with 2 Year Warranty

## 9.6W/10W OPAL CLASSIC LED



**WATTAGE > 9.6W/10W**

**LUMENS > 1055**

**HOURS LAMP LIFE > 15,000**

**DIMMABLE > NO**

**COLOUR TEMP. > 2800K**

**LAMP BASE > E27/B22**

### MEGAMAN® ECONOMY 10W OPAL

**CLASSIC** is a high lumen classic shaped LED lamp with intelligent heat sink design. The lamp has even light distribution with 330° illumination and excellent colour rendering of Ra80 or above. Eco-conscious replacement for less energy efficient halogens and incandescent lamps.

Applications:  
General domestic and commercial

### LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142532	10W	2800K / 80	1055	N	E27	105	15,000	38	109x60
142534E	9.6W	2700K / 80	1055	N	B22	109	15,000	39	107x60

**OPAL CLASSIC LED | ECONOMY SERIES** with 2 Year Warranty

## 9.6W OPAL | CLASSIC 10 PACK LED



**GREAT  
VALUE  
10 PACK**



**WATTAGE > 9.6W**

**LUMENS > 1055**

**HOURS LAMP LIFE > 15,000**

**DIMMABLE > NO**

**COLOUR TEMP. > 2700K/4000K**

**LAMP BASE > E27/B22**

**MEGAMAN® SERIES** bring you really great value with this **10 pack of 9.6W Opal Classic** lamps, with their intelligent heat sink design for sleek classic shape. The lamp has even light distribution with 330° illumination and an impressive 1055 lumen output.

Applications:  
General domestic and commercial

### LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
710466E	9.6W	2700K / 80	1055	N	E27	109	15,000	27	109x60
710464E	9.6W	2700K / 80	1055	N	B22	109	15,000	27	107x60
710467E	9.6W	4000K / 80	1055	N	E27	109	15,000	27	109X60
710465E	9.6W	4000K / 80	1055	N	B22	109	15,000	27	107X60

OPAL CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

14W OPAL CLASSIC LED







2YR

WARRANTY



WATTAGE > 14W

LUMENS > 1521

HOURS LAMP LIFE > 15,000

DIMMABLE > NO

COLOUR TEMP. > 2800K

LAMP BASE > E27/B22

**MEGAMAN® ECONOMY 10W OPAL CLASSIC** is a high lumen classic shaped LED lamp with intelligent heat sink design. The lamp has even light distribution with 330° illumination and excellent colour rendering of up to Ra80. Eco-conscious replacement for less energy efficient halogens and incandescent lamps.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
148392	14W	2800K / 80	1521	N	E27	108	15,000	69	114x60
148390	14W	2800K / 80	1521	N	B22	108	15,000	67	114x60

OPAL CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

6W OPAL DIMMING CLASSIC LED



- WATTAGE > 6W
- LUMENS > 470
- HOURS LAMP LIFE > 25,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K
- LAMP BASE > E27/B22

**MEGAMAN® ECONOMY 6W OPAL CLASSIC** a high lumen classic shaped LED lamp with intelligent heat sink design. The lamp has even light distribution with 330° illumination and excellent colour rendering of Ra90 or above. Eco-conscious replacement for halogens and incandescent lamps.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142570	6W	2800K / 90	470	Y	B22	78	25,000	39	107x60
142568	6W	2800K / 90	470	Y	E27	78	25,000	39	109x60

MEGAMAN® LED LAMPS | OPAL CLASSIC LED

OPAL CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

8.5W/9.5W OPAL DIMMING CLASSIC LED



- WATTAGE > 8.5W/9.5W
- LUMENS > 810
- HOURS LAMP LIFE > 25,000
- DIMMABLE > YES
- COLOUR TEMP. > 2700K/4000K
- LAMP BASE > E27/B22

**MEGAMAN® ECONOMY 9.5W OPAL CLASSIC** a high lumen classic shaped LED lamp with intelligent heat sink design. The lamp has even light distribution with 330° illumination and excellent colour rendering of up to Ra90. Eco-conscious replacement for halogens and incandescent lamps.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
711181	8.5W	2700K / 80	810	Y	B22	95	25,000	49	107x60
142576	9.5W	4000K / 90	810	Y	E27	85	25,000	49	107x60
711182	8.5W	2700K / 80	810	Y	B22	95	25,000	49	109x60
142578	9.5W	4000K / 90	810	Y	E27	85	25,000	49	109x60

OPAL CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

13.3W OPAL DIMMING CLASSIC LED











2YR  
WARRANTY



WATTAGE > 13.3W

LUMENS > 1055

HOURS LAMP LIFE > 25,000

DIMMABLE > YES

COLOUR TEMP. > 2800K

LAMP BASE > E27/B22

**ECONOMY SERIES 6W OPAL DIMMING CLASSIC** a high lumen classic shaped LED lamp with intelligent heat sink design. The lamp has even light distribution with 330° illumination and excellent colour rendering of Ra90 or above. Eco-conscious replacement for halogens and incandescent lamps.

Applications:  
General domestic and commercial

LAMP BASE





Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142582	13.3W	2800K / 90	1055	Y	B22	79	25,000	93	112x60
142580	13.3W	2800K / 90	1055	Y	E27	79	25,000	93	114x60

## OPAL CLASSIC LED | ECONOMY SERIES with 2 Year Warranty





10W OPAL DIMMING CLASSIC LED



- WATTAGE > 10W
- LUMENS > 810
- HOURS LAMP LIFE > 25,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K
- LAMP BASE > E27

**ECONOMY SERIES 6W OPAL DIMMING CLASSIC** a high lumen classic shaped LED lamp with intelligent heat sink design. The lamp has even light distribution with 330° illumination and excellent colour rendering of Ra80 or above. Eco-conscious replacement for halogens and incandescent lamps.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
148174	10W	2800K / 80	810	Y	E27	81	25,000	125	117x60

CANDLE LED | ECONOMY SERIES with 2 Year Warranty

2.9W/3.5W OPAL CANDLE LED



- WATTAGE > 2.9W/3.5W
- LUMENS > 250
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K/2800K
- LAMP BASE > E27/B22/E14/B15

**MEGAMAN® ECONOMY 3.5W OPAL CANDLE** is suitable for a wide variety of applications such as chandeliers, wall lights and other decorative fittings. The new lamp has an even light distribution with 330° illumination.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
143300E	2.9W	2700K / 80	250	N	E14	86	15,000	18	107x35
143302	3.5W	2800K / 80	250	N	E27	71	15,000	21	107x35
143304E	2.9W	2700K / 80	250	N	B15	86	15,000	19	105x35
143306	3.5W	2800K / 80	250	N	B22	71	15,000	23	105x35

CANDLE LED | ECONOMY SERIES with 2 Year Warranty

5.5W OPAL CANDLE LED



- WATTAGE > 5.5W
- LUMENS > 470
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > E27/B22/E14/B15

MEGAMAN® ECONOMY 5.5W OPAL CANDLE is suitable for a wide variety of applications such as chandeliers, wall lights and other decorative fittings. The new lamp has an even light distribution with 330° illumination.

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
143308	5.5W	2800K / 80	470	N	E14	85	15,000	22	107x35
143310	5.5W	2800K / 80	470	N	E27	85	15,000	26	107x35
143312	5.5W	2800K / 80	470	N	B15	85	15,000	23	105x35
143314	5.5W	2800K / 80	470	N	B22	85	15,000	27	105x35
143350	5.5W	4000K / 80	470	N	E14	85	15,000	22	107x35
143352	5.5W	4000K / 80	470	N	E27	85	15,000	26	107x35
143354	5.5W	4000K / 80	470	N	B15	85	15,000	23	105x35
143356	5.5W	4000K / 80	470	N	B22	85	15,000	27	105x35

**CANDLE LED | ECONOMY SERIES** with 2 Year Warranty

## 2.9W/3.8W OPAL DIMMING CANDLE LED



**WATTAGE > 2.9W/3.8W**

**LUMENS > 250**

**HOURS LAMP LIFE > 25,000**

**DIMMABLE > YES**

**COLOUR TEMP. > 2700K/2800K**

**LAMP BASE > E27/B22/E14/B15**

**MEGAMAN® ECONOMY 3.8W OPAL DIMMING CANDLE** is suitable for a wide variety of applications such as chandeliers, wall lights and other decorative fittings. The new lamp has an even light distribution with 330° illumination excellent colour rendering of up to Ra90.

Applications:  
General domestic and commercial

### LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142544	3.8W	2800K / 90	250	Y	B22	65	25,000	30	105x35
142546	3.8W	2800K / 90	250	Y	B15	65	25,000	33	105x35
711163	2.9W	2700K / 80	250	Y	E14	86	25,000	27	107x35
142550	3.8W	2800K / 90	250	Y	E27	65	25,000	34	107x35

CANDLE LED | ECONOMY SERIES with 2 Year Warranty

5.5W OPAL DIMMING CANDLE LED



- WATTAGE > 5.5W
- LUMENS > 470
- HOURS LAMP LIFE > 15,000
- DIMMABLE > YES
- COLOUR TEMP. > 2700K/2800K/4000K
- LAMP BASE > E27/B22/E14/B15

MEGAMAN® ECONOMY 5.5W OPAL CANDLE is suitable for a wide variety of applications such as chandeliers, wall lights and other decorative fittings. The new lamp has an even light distribution with 330° illumination.

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
711107	5.5W	2700K / 80	470	Y	B22	85	25,000	35	105x37
142554	5.5W	2800K / 90	470	Y	E27	85	25,000	33	107x37
711403	5.5W	2700K / 80	470	Y	E14	85	25,000	37	107x37
142564	5.5W	2800K / 90	470	Y	B15	85	25,000	28	105x37
142558	5.5W	4000K / 90	470	Y	B22	85	25,000	33	105x37
142560	5.5W	4000K / 90	470	Y	E27	85	25,000	37	107x37
711108	5.5W	4000K / 80	470	Y	E14	85	25,000	28	107x37
142566	5.5W	4000K / 90	470	Y	B15	85	25,000	35	105x37

## GOLF BALL LED

MEGAMAN® LED LAMPS | GOLF BALL LED

**GOLF BALL LED | ECONOMY SERIES** with 2 Year Warranty

## 2.9W/3.5W OPAL GOLF BALL LED



**WATTAGE > 2.9W/3.5W**

**LUMENS > 250**

**HOURS LAMP LIFE > 15,000**

**DIMMABLE > NO**

**COLOUR TEMP. > 2700K/2800K**

**LAMP BASE > E27/B22/E14/B15**

**MEGAMAN® ECONOMY 2.9W & 3.5W OPAL GOLF BALL** has an intelligent heat sink design for sleek classic shape and compact housing, perfect for a number of domestic and general commercial applications. The lamp has even light distribution with 330° illumination.

Applications:  
General domestic and commercial

### LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
<b>143390</b>	3.5W	2800K / 80	250	N	E14	71	15,000	17	87x45
<b>143392E</b>	2.9W	2700K / 80	250	N	E27	86	15,000	17	84x45
<b>143394E</b>	2.9W	2700K / 80	250	N	B22	86	15,000	19	82x45



GOLF BALL LED | ECONOMY SERIES with 2 Year Warranty

3.8W OPAL DIMMING GOLF BALL LED



- WATTAGE > 3.8W
- LUMENS > 250
- HOURS LAMP LIFE > 25,000
- DIMMABLE > YES
- COLOUR TEMP. > 2800K
- LAMP BASE > E27/B22/E14

**MEGAMAN® ECONOMY 3.8W OPAL GOLF BALL** has an intelligent heat sink design for sleek classic shape and compact housing, perfect for a number of domestic and general commercial applications. The lamp has even light distribution with 330° illumination.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142588	3.8W	2800K / 90	250	Y	B22	65	25,000	30	82x45
142584	3.8W	2800K / 90	250	Y	E14	65	25,000	29	87x45
142586	3.8W	2800K / 90	250	Y	E27	65	25,000	32	84x45

MEGAMAN® LED LAMPS | GOLF BALL LED

GOLF BALL LED | ECONOMY SERIES with 2 Year Warranty

5.5W OPAL DIMMING GOLF BALL LED



- WATTAGE > 5.5W
- LUMENS > 470
- HOURS LAMP LIFE > 25,000
- DIMMABLE > YES
- COLOUR TEMP. > 2700K/4000K
- LAMP BASE > E27/B22/E14

**MEGAMAN® ECONOMY 5.5W OPAL GOLF BALL** lamp provides a near perfect natural light and maximum richness of colour rendering of Ra80 or above; that is perfect for a number of domestic and general commercial applications. The lamp has even light distribution with 330° illumination.

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
711109	5.5W	2700K / 80	470	Y	B22	85	25,000	31	82x45
711113	5.5W	2700K / 80	470	Y	E27	85	25,000	38	84x45
711111	5.5W	2700K / 80	470	Y	E14	85	25,000	36	87x45
711110	5.5W	4000K / 80	470	Y	B22	85	25,000	31	82x45
711114	5.5W	4000K / 80	470	Y	E27	85	25,000	38	84x45
711112	5.5W	4000K / 80	470	Y	E14	85	25,000	36	87x45

MEGAMAN® LED LAMPS | GOLF BALL LED

## GLOBE LED | ECONOMY SERIES with 2 Year Warranty



GLOBE LED | ECONOMY SERIES with 2 Year Warranty

11W OPAL GLOBE  
120mm LED



- WATTAGE > 11W
- LUMENS > 1521
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > E27

**ECONOMY SERIES 10W OPAL GLOBE** has an intelligent heat sink design for sleek globe shape. The lamp has even light distribution with 330° illumination.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142634	11W	2800K / 80	1521	N	E27	138	15,000	102	172x124
142636	11W	4000K / 80	1521	N	E27	138	15,000	102	172x124

## FILAMENT LED

**CLASSIC GLS  
DECORATIVE CANDLE  
CLASSIC GOLF BALL  
ST64**

4.8W FILAMENT CLASSIC LED



- WATTAGE > 4.8W
- LUMENS > 470
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E27

ECONOMY SERIES 4.8W FILAMENT CLASSIC is designed for decorative light fittings, to create a charming and stunning visual effect.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146210	4.8W	2700K / 80	470	N	E27	97	15,000	31	104x60

MEGAMAN® LED LAMPS | FILAMENT CLASSIC LED

FILAMENT CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

6.8W FILAMENT CLASSIC LED



- WATTAGE > 6.8W
- LUMENS > 810
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E27/B22

ECONOMY SERIES FILAMENT CLASSIC

LED lamps are designed for decorative light fittings, to create a charming and stunning visual effect.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146212E	6.8W	2700K / 80	810	N	E27	119	15,000	34	104x60
707171E	6.8W	2700K / 80	810	N	B22	119	15,000	35	102x60



FILAMENT CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

7.2W FILAMENT DIMMING CLASSIC LED

Rich Colour  
Ra≥90

Dimmable

13  
WARRANTY  
RECALL GROUP

PER BOX  
1/60

2YR  
WARRANTY



WATTAGE > 7.2W

LUMENS > 810

HOURS LAMP LIFE > 15,000

DIMMABLE > YES

COLOUR TEMP. > 2700K

LAMP BASE > E27

ECONOMY SERIES FILAMENT CLASSIC

LED lamps are designed for decorative light fittings, to create a charming and stunning visual effect with maximum richness of colour of rendering of Ra90 or above; that is perfect for a number of domestic and general commercial applications.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146218	7.2W	2700K / 90	810	Y	E27	112	15,000	34	104x60

FILAMENT CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

8.5W FILAMENT CLASSIC LED



- WATTAGE > 8.5W
- LUMENS > 1055
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E27/B22

**ECONOMY SERIES FILAMENT CLASSIC**  
LED lamps are designed for decorative light fittings, to create a charming and stunning visual effect with colour with rendering of Ra80 or above. Perfect for a number of domestic and general commercial applications.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146214	8.5W	2700K / 80	1055	N	E27	124	15,000	34	104x60
710337	8.5W	2700K / 80	1055	N	B22	124	15,000	35	102x60

FILAMENT CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

9.5W FILAMENT CLASSIC LED

Rich Colour  
Ra=90

Dimmable

13  
HOURS  
BURNING GROUP

PER BOX  
1/60

2YR  
WARRANTY



- WATTAGE > 9.5W
- LUMENS > 1055
- HOURS LAMP LIFE > 15,000
- DIMMABLE > YES
- COLOUR TEMP. > 2700K
- LAMP BASE > E27/B22

ECONOMY SERIES FILAMENT CLASSIC

LED lamps are designed for decorative light fittings, to create a charming and stunning visual effect with colour rendering of Ra90 or above; making this a perfect LED lamp for a number of domestic and general commercial applications.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
710338	9.5W	2700K / 90	1055	Y	B22	111	15,000	35	102x60
146220	9.5W	2700K / 90	1055	Y	E27	111	15,000	34	104x60

FILAMENT CLASSIC LED | ECONOMY SERIES with 2 Year Warranty

11W FILAMENT CLASSIC LED

13  
PIECES  
ECONOMY GROUP

PER  
BOX  
1/60

2YR  
WARRANTY



- WATTAGE > 11W
- LUMENS > 1521
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E27/B22

ECONOMY SERIES FILAMENT CLASSIC

LED lamps are designed for decorative light fittings, to create a charming and stunning visual effect.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146216	11W	2700K / 80	1521	N	E27	138	15,000	45	128x70
710339	11W	2700K / 80	1521	N	B22	138	15,000	46	126x70

3W FILAMENT CANDLE LED



- WATTAGE > 3W
- LUMENS > 250
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E27/B22/E14

**MEGAMAN® ECONOMY 3W FILAMENT CANDLE** is part of the great performance and value for money Megaman LED filament range. Specifically designed for decorative light fittings, to create a charming and stunning visual effect when an exposed lamp is required.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
143264	3W	2700K / 80	250	N	E27	83	15,000	18	95x35
143919	3W	2700K / 80	250	N	B22	83	15,000	18	93x35
146222	3W	2700K / 80	250	N	E14	83	15,000	18	97x35

FILAMENT CANDLE LED | ECONOMY SERIES with 2 Year Warranty

4W FILAMENT CANDLE LED

03  
PRODUCT  
ECONOMY GROUP

  
PER  
BOX  
1/60

2YR  
WARRANTY



- WATTAGE > 4W
- LUMENS > 470
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E27/B22/E14/B15

**MEGAMAN® ECONOMY 4W FILAMENT CANDLE** is part of the great performance and value for money Megaman LED filament range. Specifically designed for decorative light fittings, to create a charming and stunning visual effect when an exposed lamp is required.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
709927	4W	2700K / 80	470	N	E27	117	15,000	18	95x35
710505	4W	2700K / 80	470	N	B15	117	15,000	16	93x35
710506	4W	2700K / 80	470	N	B22	117	15,000	18	93x35
146224	4W	2700K / 80	470	N	E14	117	15,000	15	97x35

FILAMENT CANDLE LED | ECONOMY SERIES with 2 Year Warranty

4.2W/5.3W FILAMENT DIMMING CANDLE LED



- WATTAGE > 4.2W/5.3W
- LUMENS > 470
- HOURS LAMP LIFE > 15,000
- DIMMABLE > YES
- COLOUR TEMP. > 2700K
- LAMP BASE > E27/B22/E14/B15

**MEGAMAN® ECONOMY 4.2W/5.3W FILAMENT CANDLE** is part of the great performance and value for money Megaman LED filament range. Specifically designed for decorative light fittings, to create a charming and stunning visual effect when an exposed lamp is required.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146226E	4.2W	2700K / 80	470	Y	E14	111	15,000	15	97x35
710507E	4.2W	2700K / 80	470	Y	E27	111	15,000	18	95x35
710508	5.3W	2700K / 90	470	Y	B15	88	15,000	16	95x35
710509E	4.2W	2700K / 80	470	Y	B22	111	15,000	18	93x35

MEGAMAN® LED LAMPS | FILAMENT CANDLE LED



FILAMENT GOLF BALL | ECONOMY SERIES with 2 Year Warranty

3W FILAMENT CLASSIC GOLF BALL LED



- WATTAGE > 3W
- LUMENS > 250
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E14

**MEGAMAN® ECONOMY 3W FILAMENT GOLF BALL** is part of the great performance and value for money Megaman LED filament range. Specifically designed for decorative light fittings, to create a charming and stunning visual effect when an exposed lamp is required.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146228	3W	2700K / 80	250	N	E14	83	15,000	15	79x45

MEGAMAN® LED LAMPS | FILAMENT GOLF BALL LED

FILAMENT GOLF BALL | ECONOMY SERIES with 2 Year Warranty

4W FILAMENT CLASSIC GOLF BALL LED



- WATTAGE > 4W
- LUMENS > 470
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E14

**MEGAMAN® ECONOMY 4W FILAMENT GOLF BALL** is part of the great performance and value for money Megaman LED filament range. Specifically designed for decorative light fittings, to create a charming and stunning visual effect when an exposed lamp is required.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146230	4W	2700K / 80	470	N	E14	117	15,000	17	79x45

MEGAMAN® LED LAMPS | FILAMENT GOLF BALL LED

FILAMENT GOLF BALL | ECONOMY SERIES with 2 Year Warranty

## 4.2W FILAMENT CLASSIC DIMMING GOLF BALL LED



WATTAGE &gt; 4.2W

LUMENS &gt; 470

HOURS LAMP LIFE &gt; 15,000

DIMMABLE &gt; YES

COLOUR TEMP. &gt; 2700K

LAMP BASE &gt; E14

**MEGAMAN® ECONOMY 4.2W**

**FILAMENT GOLF BALL** is part of the great performance and value for money Megaman LED filament range with colour rendering of Ra80 or above. Specifically designed for decorative light fittings, to create a charming and stunning visual effect when an exposed lamp is required.

Applications:  
General domestic and commercial

## LAMP BASE



Order Code	Watts	Colour Temp (K) / CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
711385	4.2W	2700K / 80	470	Y	E14	111	15,000	17	79x45

FILAMENT ST64 LED | ECONOMY SERIES with 2 Year Warranty

1.9W GOLD FILAMENT ST64 LED



- WATTAGE > 1.9W
- LUMENS > 200
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2000K
- LAMP BASE > E27

**THE 1.9W ECONOMY GOLD FILAMENT ST64** lamp is part of the great performance and value for money Megaman LED filament range. Specifically designed for decorative light fittings, to create a charming and stunning visual effect when an exposed lamp is required.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146238	1.9W	2000K / 80	200	N	E27	111	15,000	47	140x64

MEGAMAN® LED LAMPS | FILAMENT ST64 LED

FILAMENT ST64 LED | ECONOMY SERIES with 2 Year Warranty

4.5W FILAMENT ST64 LED



- WATTAGE > 4.5W
- LUMENS > 470
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E27

**THE MEGAMAN 4.5W ST64 FILAMENT LED** is designed with a 2700K colour temperature to provide a warm illumination perfect for creating mood lighting. This new trendy decorative lamp range is perfect for restaurant and bar applications.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146234	4.5W	2700K / 80	470	N	E27	104	15,000	44	140x64

FILAMENT ST64 LED | ECONOMY SERIES with 2 Year Warranty

7W FILAMENT ST64 LED



- WATTAGE > 7W
- LUMENS > 810
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2700K
- LAMP BASE > E27

**THE MEGAMAN 7W ST64 FILAMENT LED** is designed with a 2700K colour temperature to provide a warm illumination perfect for creating mood lighting. This new trendy decorative lamp range is perfect for restaurant and bar applications.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
146236	7W	2700K / 80	810	N	E27	115	15,000	47	140x64

MEGAMAN® LED LAMPS | FILAMENT ST64 LED

**T8 TUBE LED | PROFESSIONAL SERIES** with 3 Year Warranty





T8 TUBE LED | PROFESSIONAL SERIES with 3 Year Warranty

9W/16W/23W T8 TUBE LED



\*T8B10



\*T8B12



\*T8B14



- WATTAGE > 9W/16W/23W
- LUMENS > 920-2400
- HOURS LAMP LIFE > 30,000
- DIMMABLE > NO
- COLOUR TEMP. > 4000K
- LAMP BASE > G13

THE MEGAMAN LED TUBE is compatible with traditional magnetic ballasts making it a perfect alternative to traditional T8 fluorescent tubes.

Requires use of starter replacement, and shouldn't usually require re-wiring.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
174110	9W	4000K / 80	920	N	G13	102	30,000	105	603x28 (2ft)
174112	16W	4000K / 80	1700	N	G13	106	30,000	194	1212x28 (4ft)
174114	23W	4000K / 80	2400	N	G13	104	30,000	230	1513x28 (5ft)

PAR30s LED | ECONOMY SERIES with 2 Year Warranty

10.5W PAR30s LED




- WATTAGE > 10.5W
- LUMENS > 700
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > E27

MEGAMAN'S PAR30s is a direct replacement for the traditional halogen PAR30s in size and shape. With diffuser glass design, it delivers even light distribution.

Applications:  
General domestic and commercial

141825 / 141846



LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
141825	10.5W	2800K / 80	700	N	E27	66	15,000	102	88x95
141846	10.5W	4000K / 80	700	N	E27	66	15,000	102	88x95

GX53 LED | ECONOMY SERIES with 2 Year Warranty

5W GX53 LED



- WATTAGE > 5W
- LUMENS > 300
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > GX53

**ECONOMY SERIES GX53** is a slim profile lamp, designed for surface mounted and recessed cabinet lighting.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
147365	5W	2800K / 80	300	N	GX53	60	15,000	43	24x75
147379	5W	4000K / 80	300	N	GX53	60	15,000	43	24x75

GX53 LED | ECONOMY SERIES with 2 Year Warranty

6W GX53  
LED



- WATTAGE > 6W
- LUMENS > 520
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K/4000K
- LAMP BASE > GX53

**ECONOMY SERIES 6W GX53** is a slim profile lamp, designed for surface mounted and recessed cabinet lighting.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
147540	6W	2800K / 80	520	N	GX53	86	15,000	56	24x75
147542	6W	4000K / 80	520	N	GX53	86	15,000	56	24x75

G9 LED | ECONOMY SERIES with 2 Year Warranty

2W G9  
LED



- WATTAGE > 2W
- LUMENS > 180
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K
- LAMP BASE > G9

MEGAMAN® 2W GU9 LED is the perfect eco-saving replacement for energy hungry Halogen G9s. Thanks to their intelligently designed profiles, our G9 LED range is able to fit easily into the compact luminaires they're designed to fit into..

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142400	2W	2800K / 80	180	N	G9	90	15,000	7	43x19

G9 LED | ECONOMY SERIES with 2 Year Warranty

3.5W G9 DIMMING  
LED

WATTAGE &gt; 3.5W

LUMENS &gt; 300

HOURS LAMP LIFE &gt; 15,000

DIMMABLE &gt; YES

COLOUR TEMP. &gt; 2800K

LAMP BASE &gt; G9

**MEGAMAN® 2W G9 LED** is the perfect eco-saving replacement for energy hungry Halogen G9s. Thanks to their intelligently designed profiles, our G9 LED range is able to fit easily into the compact luminaires they're designed to fit into..

Applications:  
General domestic and commercial

## LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142403	3.5W	2800K / 80	300	Y	G9	85	15,000	7	55x18

G4 LED | ECONOMY SERIES with 2 Year Warranty

1.8W G4  
LED



- WATTAGE > 1.8W
- LUMENS > 180
- HOURS LAMP LIFE > 15,000
- DIMMABLE > NO
- COLOUR TEMP. > 2800K
- LAMP BASE > G4

MEGAMAN® latest **G4 LED** lamp is now even smaller, which means it is now suitable for even more decorative fittings. Utilising revolutionary back to back mounted LED chips, meaning it performs exactly the same as the halogen lamp it was designed to replace.

Applications:  
General domestic and commercial

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
142950	1.8W	2800K / 80	180	N	G4	100	15,000	2	37x10



CLUSTERLITE® | PROFESSIONAL SERIES with 3 Year Warranty

27W /32W/33W CLUSTERLITE®  
ACTIVE COOLING LED



- WATTAGE > 27W/32W/33W
- LUMENS > 2800-5000
- HOURS LAMP LIFE > 35,000
- DIMMABLE > NO
- COLOUR TEMP. > 4000K
- LAMP BASE > E27

MEGAMAN® CLUSTERLITE® offers impressive lumen output, making it the perfect replacement for metal halide lamps. Immense illumination output for large-scale commercial and industrial applications. Active cooling promotes better control of the thermals allowing for improved lamp performance, efficiency and life.

Applications:  
Large-scale and demanding commercial applications

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
804602	27W	4000K / 80	2800	N	E27	103	35,000	304	195x63
804604	32W	4000K / 80	4160	N	E27	130	35,000	310	195x63
804606	33W	4000K / 80	5000	N	E27	151	35,000	308	195x63

CLUSTERLITE® | PROFESSIONAL SERIES with 3 Year Warranty

46W CLUSTERLITE®  
ACTIVE COOLING LED



- WATTAGE > 46W
- LUMENS > 7000
- HOURS LAMP LIFE > 35,000
- DIMMABLE > NO
- COLOUR TEMP. > 4000K
- LAMP BASE > E27

MEGAMAN® CLUSTERLITE® offers impressive lumen output, making it the perfect replacement for metal halide lamps. Immense illumination output for large-scale commercial and industrial applications. Active cooling promotes better control of the thermals allowing for improved lamp performance, efficiency and life.

Applications:  
Large-scale and demanding commercial applications

LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
804608	46W	4000K / 80	7000	N	E27	152	35,000	367	225x63

MEGAMAN® LED LAMPS | CLUSTERLITE® LED

CLUSTERLITE® | PROFESSIONAL SERIES with 3 Year Warranty

# 32W CLUSTERLITE®

## PASSIVE COOLING LED



WATTAGE &gt; 32W

LUMENS &gt; 4200

HOURS LAMP LIFE &gt; 30,000

DIMMABLE &gt; NO

COLOUR TEMP. &gt; 4000K

LAMP BASE &gt; E27

**MEGAMAN® 32W CLUSTERLITE® LED** offers impressive lumen output, making it the perfect replacement for metal halide lamps. Immense illumination output for large-scale commercial and industrial applications. Passive cooling promotes simpler design, along with no running noise.

Applications:  
Large-scale and demanding commercial applications

### LAMP BASE



Order Code	Watts	Colour Temp (K) /CRI	Lumens (lm)	Dimmable	Lamp Base	Lumen/ Watts	Hrs Lamp Life (max)	Weight (g)	Dimensions (LxDia mm)
804610	32W	4000K / 80	4200	N	E27	131	30,000	311	195x63

# PRODUCT INDEX

## LED FIXTURES


**Find the MEGAMAN® LED Fixtures  
you are looking for by using either  
product order code or product name.**

## PRODUCT INDEX | LED FIXTURES

ORDER CODE	PAGE NUMBER								
130212	6	142616	110	146230	145	164014	41	190796	25
130212	60	142618	110	146234	148	164022	41	190798	25
130214	6	142620	111	146236	149	174110	151	190800	22
130214	60	142622	111	146238	147	174112	151	190800	24
130340	7	142624	112	147365	153	174114	151	191000	23
130342	7	142626	112	147379	153	180294	12	191002	23
140500	99	142630	108	147540	154	180342	19	191004	23
140502	99	142632	108	147542	154	180344	19	191006	23
140504	104	142634	133	148174	123	180346	19	191008	23
140506	104	142636	133	148390	118	180348	19	519030	29
140508	104	142950	157	148392	118	180350	19	519036	28
140510	98	143264	141	161001	43	180360	21	519038	28
140512	98	143300	124	161003	43	180362	21	519040	28
140514	98	143302	124	161004	43	180364	21	519042	28
140516	107	143304	124	161006	43	180366	21	707171	136
140518	107	143306	124	161011	42	180368	21	709927	142
140520	107	143308	125	161013	42	180370	21	710264	15
140522	105	143310	125	161014	42	180372	21	710267	14
140524	105	143312	125	161016	42	180374	21	710274	15
140526	105	143314	125	161017	42	180376	21	710286	14
141510	101	143316	115	161019	42	180378	21	710286	16
141580	101	143318	115	161020	42	180380	19	710297	17
141825	152	143350	125	161022	42	180382	19	710298	17
141846	152	143352	125	161023	42	180384	19	710325	17
142220	103	143354	125	161025	42	180386	19	710327	17
142222	103	143356	125	161026	42	180388	19	710337	138
142224	103	143360	114	161028	42	180390	19	710338	139
142400	155	143362	114	161029	42	180392	19	710339	140
142403	156	143370	115	161031	42	180394	19	710354	16
142532	116	143372	115	161032	42	180396	19	710386	17
142534	116	143374	115	161034	42	180398	19	710387	17
142544	126	143376	115	161035	42	190550	9	710390	100
142546	126	143390	129	161037	42	190552	9	710391	100
142550	126	143392	129	161038	42	190554	9	710430	15
142554	127	143394	129	161040	42	190556	9	710437	16
142558	127	143919	141	161041	42	190574	8	710438	16
142560	127	144000	106	161043	42	190576	8	710464	117
142564	127	144002	106	161044	42	190578	8	710465	117
142566	127	144004	39	161046	42	190580	8	710466	117
142568	119	144006	39	161047	42	190582	8	710467	117
142570	119	146210	135	161047	42	190584	8	710474	84
142576	120	146212	136	161049	42	190586	8	710476	85
142578	120	146214	138	161050	42	190588	8	710478	85
142580	121	146216	140	161052	42	190706	10	710479	85
142580	122	146218	137	161053	42	190740	22	710480	88
142582	121	146220	139	161053	42	190740	24	710481	89
142582	122	146222	141	161055	42	190742	22	710482	90
142584	130	146224	142	164004	37	190742	24	710483	91
142586	130	146226	143	164006	37	190750	22	710485	92
142588	130	146228	144	164010	41	190750	24	710487	86

## PRODUCT INDEX | LED FIXTURES

ORDER CODE	PAGE NUMBER					PRODUCT NAME	PAGE NUMBER
710488	87	711088	26	711346	26	BERTO	7
710489	86	711102	22	711347	22	BERTO	61
710489	87	711107	127	711365	127	DINO 2	23
710491	85	711108	127	711366	127	DINO FARM	25
710492	86	711109	131	711385	131	EKON	32
710492	87	711110	131	711403	131	ESTELA 2	33
710505	142	711111	131	711411	131	FARRON	21
710506	142	711112	131	711412	131	FONDA	17
710507	143	711113	131	711413	131	GABIO	9
710508	143	711114	131	711417	131	GARRON	73
710509	143	711126	77	711418	77	GEO 2	11
710675	61	711128	77	711419	77	KANA	81
710676	61	711140	77	711420	77	KATIA	69
710677	13	711142	77	711421	77	KEO	63
710689	31	711163	126	790704	126	MARCO	41
710691	31	711181	120	804602	120	MARCO MIDI	39
710709	31	711182	120	804604	120	MARCO MINI	37
710729	10	711183	27	804606	27	MILENA	31
710830	12	711260	63	804608	63	MILENALITE	79
710842	10	711261	63	804610	63	RENZO	15
710871	79	711263	63	710502BACKLIT	63	ROCCA	75
710872	79	711264	62	710502SIDELIT	62	RONDA	71
710873	79	711285	65	710502BACKLIT	65	TEGO	29
710874	79	711286	65	710502SIDELIT	65	TEGO 2	27
710875	79	711288	65			TEGO SLIM	77
710876	79	711289	65			TITO	32
710889	13	711291	65			TONO	19
710890	13	711292	67			TOTT 2	13
710891	13	711293	67			VOSS	65
710931	11	711295	67			VOSS	67
710933	6	711320	62			XAVIER	33
710933	60	711321	62				
710940	6	711322	62				
710940	60	711323	62				
710941	6	711329	69				
710941	60	711330	69				
710971	10	711331	69				
711044	54	711332	69				
711045	55	711334	73				
711046	52	711335	73				
711047	53	711336	73				
711048	56	711337	73				
711049	49	711338	73				
711050	48	711339	73				
711051	47	711340	73				
711052	46	711341	73				
711081	61	711342	75				
711082	61	711343	75				
711085	26	711344	75				
711087	26	711345	75				



MEGAMAN® PERFORMA  
FONDA. Plug-and-play IP66  
and IK10 LED bulkhead.

Go to page 16 to see the full details.






**GU10 LED | ECONOMY SERIES** with 2 Year Warranty

**GEO 2 IP65 LED HIGH BAY with Selectable Wattage**

36-150W | 4000K | 10500-21000lm | 50,000hrs | Dimmable





**MEGAMAN®**

Megaman (UK) Limited  
Megaman House  
2 Quadrant Park  
Mundells  
Welwyn Garden City  
Herts AL7 1FS

T: +44 (0)1707 386000  
F: +44 (0)1707 386001  
E: [sales@megamanuk.com](mailto:sales@megamanuk.com)



Follow us  
[@megamanukltd](https://twitter.com/megamanukltd)

© MEGAMAN® (UK) LTD APRIL 2022

All information stated is correct at the time  
of printing and subject to change without  
prior notice.

